


精密型 快插接头

弯接头/加长弯接头 外螺纹


代码	类型	材质			表面处理
		主体	螺纹部	脱离环部	主体
J-XXD01	外螺纹	PBT	黄铜	POM	镀镍
J-XXD02			SUS304		—
J-XXD06		黄铜	黄铜		镀镍



弯接头
J-XXD01
J-XXD02



加长弯接头
J-XXD06



视角标准：第一视角

弯接头

型号	公称	R	A	B	L	P	C	E	S	有效断面积	重量
代码	D	型号								(mm²)	(g)
J-XXD01 J-XXD02	4	M5	M5	3.5	18.5	20.5				1.57	7.99
		1	R1/8	7.5	21	22.6	11	14.9	18.5	12	8.9
		2	R1/4	10	24	23.4				14	12.8
	6	M5	M5	3.5	19.5	22.5				1.57	8.7
		1	R1/8	7.5	22	24.5	13	17	19.5	12	9.7
		2	R1/4	10	25	25.2				14	13.6
	8	3	R3/8	10.5	26	25.8				17	19.0
		1	R1/8	7.5	25	27.9	14.5	18.1	23	14	16.58
		2	R1/4	10	27.5						15.3
	10	3	R3/8	10.5	28.5	28.8	14.4				20.7
		1	R1/8	7.5	27.5	32	18.6			17	16.58
		2	R1/4	10	30	32.5		20.2	27		31.79
	12	3	R3/8	10.5	30.5		18.5				26.1
		4	R1/2	13.5	34	34.3				21	37.1
		2	R1/4	10	30.5	34.4					31.79
	12	3	R3/8	10.5	31	34.6	21.4	23.4	29.5	17	28.2
		4	R1/2	13.5	34.5	36.3				21	39.2

加长弯接头

型号	公称	R	A	B	L	P	C	E	S	有效断面积	重量
代码	D	型号								(mm²)	(g)
J-XXD06	4	M5	M5	3.5	30.5	32.5	11	14.9	18.5	12	18.7
		1	R1/8	7.5	33	34.6					18.3
		2	R1/4	10	36	38.3	13	17	19.5	12	20.5
	6	3	R3/8	10.5	40	39.6	13.1			14	25.6
		1	R1/8	7.5	43	44.5				17	35.9
		2	R1/4	10	43	43.5	14.4	18.1	23	14	30.7
	8	3	R3/8	10.5	44	44.1	14.5				28.9
		2	R1/4	10	49.5		18.6				39.4
		3	R3/8	10.5	50	52	18.4	20.2	27	17	53.6
	10	4	R1/2	13.5	53.5	56.2	18.6				48.9
		2	R1/4	10	52.5		57	23.4	29.5	21	72.7
		3	R3/8	10.5	53						59.6
	12	4	R1/2	13.5	56.5	55.9	21.3				54.5
		3	R3/8	10.5	53						54.5
		4	R1/2	13.5	56.5	55.9	21.3			21	78.8

弯接头(黄铜)

型号	公称	R
代码	D	型号
J-XXD01	4	M5
	1	R1/8

J-XXD01 - D4 - M5



未税价(元)

优惠价
数量 1~29 30~
价格 100% 另行报价

交货期
1



请按图示订货

气
调
速
接
头
类
D8