

外螺纹·外圈滑动表面带保护层


正常系列(POS...)(SA...T/K)(NOS...)

杆端关节轴承



代码	类型	注油式	杆端		衬垫	内圈	
			材质	表面处理		材质	热处理
BNC50	外螺纹	自润滑	碳钢	镀环保白锌	铜	轴承钢	淬火
BNC51							
BNC52							
BNC53							



注油式
BNC50



自润滑
BNC51
BNC52
BNC57



注油式(POS...)

代码	型号	轴承规格	螺纹 旋向	d	B	d _K	C ₁	d ₂	G(6H)	h	L ₁ (min)	L ₂	R ₁	a°≈	静态径向 载荷容量(KN)	重量 (kg)
BNC50	POS5			5	8	7.7	6	16	M5×0.8	33	20	41		13	3.43	0.0125
	POS6			6	9	9	6.75	18	M6×1.0	36	22	45		13	4.9	0.019
	POS8			8	12	10.4	9	22	M8×1.25	42	25	53		14	6.86	0.032
	POS10			10	14	12.9	10.5	26	M10×1.5	48	29	61		14	10.8	0.054
	POS12			12	16	15.4	12	30	M12×1.75	54	33	69		13	16.7	0.085
	POS12-1			12	16	15.4	12	30	M12×1.25	54	33	69		13	16.7	0.085
	POS14		R (右旋)	14	19	16.9	13.5	34	M14×2.0	60	36	77		16	20.6	0.126
	POS16		L (左旋)	16	21	19.4	15	38	M16×2.0	66	40	85		16	25	0.185
	POS16-1		L (左旋)	16	21	19.4	15	38	M16×1.5	66	40	85		16	25	0.185
	POS18			18	23	21.9	16.5	42	M18×1.5	72	44	93		15	29.4	0.26
	POS20			20	25	24.4	18	46	M20×1.5	78	47	101		15	34.3	0.34
	POS22			22	28	25.8	20	50	M22×1.5	84	51	109		15	41.2	0.435
	POS25			25	31	29.6	22	60	M24×2.0	94	57	124		15	72.5	0.65
	POS28			28	35	32.3	24	66	M27×2.0	103	62	136		15	75.5	0.96
	POS30			30	37	34.8	25	70	M30×2.0	110	66	145		17	92.2	1.07

自润滑(SA...T/K)

代码	型号	轴承规格	螺纹 旋向	d	B	C ₁	d ₂	G(6H)	h	L ₁ (min)	L ₂	R ₁ (min)	a°≈	额定负荷(KN) 动负荷 静负荷	重量 (kg)
BNC51 BNC52 BNC53	SA5T/K			5	8	6	18	M5×0.8	33	19	43.5		13	4.4 4.6	0.013
	SA6T/K*			6	9	6.75	20	M6×1.0	36	21	46.5		13	4.5 4.8	0.015
	SA8T/K*			8	12	9	24	M8×1.25	42	25	54.5		14	5.8 6.5	0.034
	SA10T/K*			10	14	10.5	28	M10×1.5	48	28	63.5		13	9.7 12	0.071
	SA12T/K*			12	16	12	32	M12×1.75	54	32	71.5		13	10.6 15	0.11
	SA14T/K*			14	19	13.5	36.5	M14×2.0	60	36	79		16	17 22	0.13
	SA16T/K*		R (右旋)	16	21	15	42	M16×2.0	66	37	87		15	19.7 27	0.22
	SA16T/K-1		R (右旋)	16	21	15	42	M16×1.5	66	37	87		15	19.7 27	0.22
	SA18T/K		L (左旋)	18	23	16.5	46	M18×1.5	72	41	96		15	31.3 35	0.29
	SA20T/K		L (左旋)	20	25	18	51	M20×1.5	78	45	104		14	29.8 40	0.36
	SA22T/K			22	28	21	54	M22×1.5	84	48	111		14	40.2 48	0.49
	SA25T/K			25	31	22	61	M24×2.0	94	55	125		15	44 55	0.65
	SA28T/K			28	35	24	66	M27×2.0	103	62	136		15	52.2 65	0.87
	SA30T/K			30	37	25	71	M30×2.0	107	66	146.5		17	60.2 78	1.1
	SA35T/K			35	43	28	81	M36×2.0	125	85	180.5		16	—	1.64
	SA40T/K			40	49	33	91	M42×2.0	142	90	195.5		17	—	2.4
	SA50T/K			50	60	45	117	M48×2.0	160	105	243.5		12	—	4.8

① BNC53仅适用带*号规格。

自润滑(NOS...)

代码	型号	轴承规格	螺纹 旋向	d	B	C ₁	d ₂	G(6H)	h	L ₁ (min)	L ₂	R ₁	a°≈	静态径向 载荷容量(KN)	重量 (kg)
BNC57	NOS3			3	6	4.5	12	M3×0.5	27	15	33		10	1.57	0.0045
	NOS4			4	7	5.3	14	M4×0.7	30	17	37		11	2.25	0.007
	NOS5			5	8	6	19	M5×0.8	33	20	42.5		13	3.43	0.0125
	NOS6			6	9	6.75	21	M6×1.0	36	22	46.5		13	4.9	0.019
	NOS8		R (右旋)	8	12	9	25	M8×1.25	42	25	54.5		14	6.86	0.032
	NOS10		L (左旋)	10	14	10.5	29	M10×1.5	48	29	62.5		14	9.41	0.054
	NOS12			12	16	12	33	M12×1.75	54	33	70.5		13	11	0.085
	NOS14			14	19	13.5	37	M14×2.0	60	36	78.5		16	15.2	0.126
	NOS16			16	21	15	43	M16×2.0	66	40	87.5		15	20.2	0.185
	NOS18			18	23	16.5	47	M18×1.5	72	44	95.5		15	25.2	0.26
	NOS20			20	25	18	51	M20×1.5	78	47	103.5		15	27.8	0.34
	NOS22			22	28	20	55	M22×1.5	84	51	111.5		15	35.9	0.435



代码	型号	轴承规格	螺纹旋向	d
BNC51	SA5T/K	R(右旋)		5
BNC51	SA6T/K	L(左旋)		6

BNC51 — SA5T/K — R



优惠价
数量 1~9 10~
价格 100% 另行报价



交货期
5

总目录

目录

使用说明

螺钉

螺栓

螺柱

铆接类

组合件

螺母

垫圈

挡圈

树脂类

带挡块

螺钉

柱塞

紧固件

进口专区

紧固件

专用配件

经济型

轴承

标准型

轴承

进口型

轴承

品牌轴承

带座轴承

吊环

索具

电子焊接

工具

手动工具

电动工具

气动工具

储存工具

量具

刀具

技术资料