




螺纹圆形连接器

方法兰插座 经济型

代码	类型	连接方式	材质			表面处理	
			外壳	绝缘体	接触体	外壳	接触体
ZIX58	经济型	方法兰插座	螺纹连接	锌合金	热塑塑料PPS (耐高温260℃)	铜	镀铬 镀金



视角标准：第一视角

型号		规格	芯数	端头	d	M	L ₁	L	B	A	D	K	适配插头 代码
代码	外壳形状												
ZIX58	Z (方法兰插座)	16	2		15.8	M18×1	9.7	21.6	20	26	16.5	3.2	ZIX46 ZIX47
			3										
			4										
			5										
			7										
			9										
		10											
		20	2	19.8	M22×1	9.8	22	29	20.5				
			3										
			4										
			5										
			6										
			7										
		24	J(插针) K(插孔)		23.8	M26×1	10	23	26	32	24.5		
			9										
			12										
			10										
			12										
			19										
		28	7	27.8	M30×1	9.8	30	36	28.5				
			12										
			16										
			17										
			20										
			24										
			26										

❗ 插针头必须和插孔头配合使用。

型号		规格	芯数	端头
代码	外壳形状			
ZIX58	Z	16	4	J(插针)
			5	K(插孔)

请按图示订货 ZIX58—Z—16—4—J

■ 性能表

连接方式	螺纹连接
接线方式	焊接
接插次数	500次
温度范围	-40℃~+85℃