

弹簧式侧面真空端口
弹簧式直接安装型

快速接头型/螺纹型


精密型 常规型真空吸盘(组件)

● 弹簧式侧面真空端口


代码	类型	接管方式	吸盘材质	颜色
J-WES31	弹簧式侧面真空端口	快速接头型	丁腈橡胶NBR	黑色
J-WES32			导电性硅橡胶SE	黑色
J-WES33			氟橡胶F	灰色




盘径 $\varnothing 2 \sim 4$




盘径 $\varnothing 6, 8$



盘径 $\varnothing 10$



盘径 $\varnothing 15 \sim 50$



视角标准：第一视角


型号	盘径d	B	D	M	L ₁	L ₂	L ₃	P	行程S	E ₁	E ₂	对边H ₁	对边H ₂	T	弹簧最大负载(N)	重量(g)	
J-WES31 J-WES32 J-WES33	2	40	4	M8×0.75	4	24	13	13	3	16.7	12.5	10	8	2	0.9~1.9	13.5	
	3																
	4																
	6	41	6	M14×1	7	25	20	16	6	18.1	13	17	12	4	4.0~7.1	48	
	8	39.5			5.5	23.5											
	10	58.1			8	35											
	15	59.1	65.1			9	36	15	42								
	20	60.1				10	37										
	25	61.1				11	38										
	30	61.1				14	41										
40	64.1	15				42											
50	65.1																

● 弹簧式直接安装型


代码	类型	接管方式	吸盘材质	颜色
J-WES36	弹簧式直接安装型	螺纹型	丁腈橡胶NBR	黑色
J-WES37			导电性硅橡胶SE	黑色
J-WES38			氟橡胶F	灰色




盘径 $\varnothing 2 \sim 4$




盘径 $\varnothing 6, 8$



盘径 $\varnothing 10$



盘径 $\varnothing 15 \sim 50$



视角标准：第一视角

型号	盘径d	B	M	A	L ₁	L ₂	P	行程S	对边H ₁	对边H ₂	弹簧最大负载(N)	重量(g)	
J-WES36 J-WES37 J-WES38	2	32	M10×1	9.5	4	22.5	14	3	12	-	2.3~3.9	14.5	
	3												
	4												
	6	30.5	M14×1	11.7	7	19	5.8	17	12	7.9~15.0	59		
	8				5.5							21	
	10				8							39.3	
	15	52	60.1			9	40.3	15	47.3				
	20	54				10	42.3						
	25	55				11	43.3						
	30	55				14	46.3						
40	58	15				47.3							
50	59												

● 弹簧式侧面真空端口

型号	代码	d	B
J-WES31-d15	J-WES31	15	59.1
	J-WES32	20	60.1

请按图示订货



未税价(元)

优惠价	数量	1~29	30~
	价格	100%	另行报价

交货期	1
	1