


精密型 耐热快速接头

- 直接头
- 内六角孔直接头
- 外螺纹

直接头

代码	类型	材质			表面处理
		主体	螺纹部	密封部材料	主体
J-XP01	外螺纹 直接头	黄铜	黄铜	耐热NBR	镀镍



型号	公称	R	D	E	B	C1	C2	A	L	S	喷嘴	有效断面	重量
代码	d	型号									直径	面积 (mm²)	(g)
J-XP01	4	M5	M5		22.5			2.8	19.8		2.4	2	8
		1	R1/8	6	9.7	23.7	17.6	15	8	19.7	3	4.5	10
		2	R1/4		—	25.2			11	19.2	14		19
	6	M5	M5		24.4			2.8	21.6		2.4	2	12
		1	R1/8	8	11.8	24.8	19.5	16.3	8	20.8	5	11	17
		2	R1/4		—	26.2			11	20.1	14		31
	8	3	R3/8		—	27			12	20.6	17		18
		1	R1/8		29.9	28.6	20.2	17.2	8	25.9	6		19
		2	R1/4	10	13.7	28.6			11	22.6	14	20	29
	10	3	R3/8		—	27.5			12	21.2	17		30
		1	R1/8		32.8	31.8	23.2	19.5	8	28.8	6	23	27
		2	R1/4	12	17.5	32.3			11	26.3	17	8.5	32
J-XP01	12	3	R3/8		—	32.9			12	25.5	9	35	54
		1	R1/8		38.9	34.9	26.3	22.3	15	24.7	21	9	51
		2	R1/4	14	20.8	34.9			11	32.9	8.5	47	45
	4	3	R3/8		—	36.9			12	28.6	21	11	59
		1	R1/8		36.9				15	28.7			
		2	R1/2										



型号	公称	R
代码	d	型号
J-XP01	4	M5
	1	R1/8

J-XP01-d4-M5





数量	1~29	30~
价格	100%	另行报价



1

内六角孔直接头

代码	类型	材质			表面处理
		主体	螺纹部	密封部材料	主体
J-XP11	外螺纹 内六角孔直接头	黄铜	黄铜	耐热NBR	镀镍



型号	公称	R	D	P ₁	P ₂	B	C ₁	C ₂	A	L	S	喷嘴 直径	有效新面积 (mm ²)	重量 (g)
代码	d	型号												
J-XP11	4	M5	M5		9.6	22.4			2.8	19.7			2	7
		1	R1/8	6	9.7	22.7	17.6	15	8	18.7	2.5	2.6	5.2	9
		2	R1/4		9.6	22.7			11	16.7				15
	6	M5	M5		11.8	23.8			2.8	21	2.5	2.6	2	9
		1	R1/8	8	11.8	24.6	19.5	16.3	8	20.6				11
		2	R1/4		13.7	23.8			11	17.7	4	4.2	11	15
	8	3	R3/8		16.8	27.9			12	17.4				24
		1	R1/8		13.7	27.9	20.2	17.2	8	23.9		5.3		13
		2	R1/4	10	13.7	27.1			11	21.1	5	6.3	17	16
	10	3	R3/8		16.8	24.2			12	19.9				23
		1	R1/8			32.8			8	28.8		5.3	23	25
		2	R1/4	12	17.5	32.3	23.2	19.5	11	26.3	6	6.3	17	29
12	3	R3/8		17.5	31.8			12	25.4				35	
	4	R1/2		20.8	32.8			15	24.6				54	
	2	R1/4			38.9			11	32.9		6.3	20	44	
	3	R3/8	14	20.8	34.9	26.3	22.3	12	28.6	5			45	
	4	R1/2			36.9			15	28.7		8.4	40	60	



型号	公称	R
代码	d	型号
J-XP11	4	M5
	1	R1/8

J-XP11-d4-M5



数量	1~29	30~
价格	100%	另行报价



1

气动接头

D8