


内六角螺栓型
 紧定螺钉型
 角座型

无弹簧定位珠

内六角螺栓型

代码	类型	主体			球头	
		材质	硬度	表面处理	材质	硬度
PKZ01	内六角螺栓型	SCM435	35~45HRC	发黑	SUJ2	53~60HRC
PKZ03		SUS304	—	—	SUS440C	55HRC~




型号	公称尺寸	L	L ₁	D	K	S	h	d	H	耐负载 (kN)	
PKZ01 PKZ03	4	10	10.5	2.1	7	4	3	2	2.5	0.8	1.3
		12	12.5								
		16	16.5								
		20	20.5								
		25	25.5								
		30	30.6								
	5	12	12.6	2.4	8.5	5	4	2.5	3	1	1.4
		16	16.6								
		20	20.6								
		25	25.6								
		30	30.6								
		40	40.8								
6	16	16.8	3	10	6	5	3	4	1.3	3.3	
	20	20.8									
	25	25.8									
	30	30.8									
	40	40.8									
	50	51.2									
PKZ01 PKZ03	8	20	21.2	3.5	13	8	6	4	5.5	1.8	3.9
		30	31.2								
		35	36.2								
		40	41.2								
		50	51.2								
		25	26.7								
	10	30	31.7	4.5	16	10	8	5	7	2.3	3.4
		40	41.7								
		50	51.7								
		60	61.7								
		30	32								
		50	52								
12	50	52	5	18	12	10	6	8.5	2.8	4.8	
	80	82									

kgf=N×0.101972

紧定螺钉型

代码	类型	主体			球头	
		材质	硬度	表面处理	材质	硬度
PKZ11	紧定螺钉型	SCM435	35~45HRC	发黑	SUJ2	53~60HRC
PKZ13		SUS304	—	—	SUS440C	55HRC~
PKZ15		相当40Cr	48HRC~	发黑	相当SUS440C	50~55HRC




型号	公称尺寸	L	d	S	V	H	耐负载 (kN)					
PKZ11 PKZ13	3	5.2	10.2	1.5	1.5	1.2	0.5	0.5				
		4	6.5	10.5	16.5	2.5	2	0.8	1.3			
		5	8.6	12.6	20.6	3	2.5	1	1.4			
		6	10.8	16.8	20.8	25.8	4	3	3.5	1.3	3.3	
		8	*11.2	13.2	21.2	26.2	31.2	5.6	4	5(2.5)	1.8	3.9
		10	*13.7	17.7	21.7	26.7	36.7	7.1	5	6(3.5)	2.3	3.4
	PKZ15	8	11.2	21.2	42	8.7	6	8(3)	2.8	4.8		
			3	5.2	10.2	1.5	1.5	2	0.5	0.5		
			4	6.5	10.5	16.5	2.38	2	2.5	0.7	1.3	
			5	8.6	12.6	20.6	3	2.5	3	0.9	1.4	
			6	10.8	16.8	20.8	25.8	3.5	3	3.5	1.2	3.3
			8	11.2	21.2	42	5	4	5	1.7	3.9	

kgf=N×0.101972

带 * L 尺寸的 V 尺寸为 () 内尺寸。

角座型

代码	类型	主体			挡块	
		材质	硬度	表面处理	材质	硬度
PKZ21	角座型	SCM435	38~43HRC	发黑	SUJ2	55HRC~
PKZ23		SUS304	—	—	SUS440C	—
PKZ25		相当40Cr	48HRC~	发黑	相当SUS440C	50~55HRC



型号	公称尺寸	L	d	S	V	H	耐负载 (kN)				
PKZ21 PKZ23	4	6	10	16	2	2	0.3	1.3			
		5	8	12	20	2.5	2.5	0.4	1.4		
		6	10	16	20	25	3.2	3	3.5	0.6	3.3
		8	10* 12	20	25	30	4.5	4	5(2.5)	0.8	3.9
		10	12* 16	20	25	35	6	5	6(3.5)	1	4.8
		12	16* 20	30	40	7.2	6	8(3)	1	4.8	
PKZ21	16	20* 25	35	50	10.7	8	10(3)	1.3	8.9		
PKZ25	4	6	10	20	2	2	2.5	0.3	1.3		
		5	8	12	20	2.5	2.5	3	0.4	1.4	
		6	10	16	25	3.2	3	3.5	0.6	3.3	
		8	12	20	25	4.5	4	5	0.8	3.9	
		10	16	25	35	6	5	6	1	4.8	
		12	20	30	40	7.2	6	8	1	4.8	

kgf=N×0.101972

带 * L 尺寸的 V 尺寸为 () 内尺寸。

内六角螺栓型

型号	公称尺寸
PKZ01	10
PKZ03	12

角座型

型号	公称尺寸
PKZ21	4
PKZ23	5
PKZ25	8



定向零件
A7