



锁紧螺母

锁紧螺母/防松动垫圈 圆型



代码	类型	销售方式	锁紧螺母		防松动垫圈	
			材质	表面处理	材质	表面处理
BKJ51	圆型	单件	SS400	发黑	—	—
BKJ61			SUS304	—	—	—
BKJ56		套件	—	—	SPCC	铬酸盐处理
BKJ57			—	—	SUS304	—
BKJ52	锁紧螺母+防松动垫圈	套件	SS400	发黑	SPCC	铬酸盐处理
BKJ62			SUS304	—	SUS304	—



锁紧螺母



防松动垫圈



视角标准：第一视角

型号		螺距	锁紧螺母							防松动垫圈						
代码	公称尺寸		D	d	H	g	t	d1	K	E	F	T	V	D1	D2	齿数
锁紧螺母 BKJ51 BKJ61	M10	0.75	18	13	4	3		10	8.5	3	3		2	21	13	9
	M12		22	17				12	10.5					25	17	
	M15	1.0	25	21				15	13.5			1		28	21	
	M17		28	24	5	4	2	17	15.5	4	4			32	24	
	M20		32	26	6			20	18.5					36	26	13
	M25		38	32	7			25	23		5			42	32	
	M30		45	38		5		30	27.5	5	5		2.5	49	38	
	M35	1.5	52	44	8			35	32.5					57	44	
	M40		58	50	9			40	37.5			1.2		62	50	15
	M45		65	56	10	6	2.5	45	42.5	6	6			69	56	
防松动垫圈 BKJ56 BKJ57	M50		70	61				50	47.5					74	61	
	M55		75	67	11			55	52.5					81	67	17
	M60		80	73		7	3	60	57.5	7				86	73	
	M65		85	79				65	62.5		8			92	79	
	M70		92	85	12			70	66.5			1.5		98	85	
	M75		98	90	13	8	3.5	75	71.5	8			4	104	90	
	M80		105	95	15			80	76.5					112	95	
	M85		110	102				85	81.5					119	102	
	M90		120	108	16			90	86.5		10			126	108	
	M95	2.0	125	113	17	10	4	95	91.5	10		1.8		133	113	
锁紧螺母+ 防松动垫圈 BKJ52 BKJ62	M100		130	120	18			100	96.5					142	120	
	M105*		140	126				105	100.5					145	126	
	M110		145	133				110	105.5			12		154	133	
	M115*		150	137	19			115	110.5				6	159	137	19
	M120		155	138	20	12	5	120	115	12				164	138	
	M125*		160	148	21			125	120		14			170	148	
	M130*		165	149				130	125			2		175	149	
	M140*		180	160	22			140	135					192	160	
	M150*		195	171	24	14	6	150	145	14	16			205	171	
	M160*		210	182	25			160	154					217	182	
	M170*		220	193	26	16	7	170	164	16	18		8	232	193	
	M180*	3.0	230	203	27			180	174			2.5		242	203	
	M190*		240	214	28	18	8	190	184	18	20			252	214	
	M200*		250	226	29			200	194					262	226	

① 锁紧螺母与对应防松动垫圈规格相匹配。

① 带“*”尺寸不适用BKJ57/BKJ61/BKJ62。



请按图示订货

型号		螺距
代码	公称尺寸	
BKJ52	M10	0.75
BKJ61	M12	1.0

BKJ51—M10—0.75



未税价(元)

● 优惠价

数量	1~4	5~
价格	100%	另行报价



交货期

3




交货期

5

① BKJ51/52/56

① BKJ61/62/57

轴加工尺寸图



加工尺寸a最小值可参考F+1值进行加工
加工尺寸b最小值可参考d1+K+0.5值进行加工



Example
使用示例

① 用于锁紧机床主轴与零件间的配合，通过垫圈进行物理锁紧可保证一定的安装精度，主要应用在机电设备。

