


代码	类型		材质		表面处理	端部	弹簧常数公差
			国标	相当			
Y CIM01	外径基准型	微型	0Cr18Ni9	SUS304	钝化	闭合不磨平	±10%
Y CIM02			琴钢丝	SWP			

- ① 压紧长度为参考值，制作时有少许差异。
- ② 两端均未进行磨削加工。
- ③ 使用次数为100万次(参考)。

D尺寸公差		L尺寸公差	
D	公差	L	公差
D ≤ 1	±0.05	L ≤ 3	±0.3
1 < D ≤ 3	±0.08	3 < L ≤ 15	±0.5
D > 3	+0.08 -0.13	L > 15	±1



型号	代码	D	L	d	压紧长度	压紧负荷(N)		弹簧常数(N/mm)		安装孔径	安装杆径
						Y CIM01	Y CIM02	Y CIM01	Y CIM02		
Y CIM01	0.6	1	1	0.65				1.97			
			1.4	0.85			1.254				
			2	1.15	0.667		0.811		0.8	0.3	
			2.7	1.55			0.552				
	0.9	0.1	3.9	2.15			0.373				
			1.5	0.65			0.481				
			2.2	0.85			0.306				
			3.2	1.15	0.408		0.198		1.1	0.5	
	1.1	0.1	4.6	1.55			0.135				
			6.6	2.15			0.091				
			2	0.65			0.246				
			2.9	0.85			0.157				
	1.2	0.2	4.4	1.15	0.325		0.101			0.7	
			6.3	1.55			0.069				
			9.2	2.15			0.047				
			2	0.65			3.94		1.4		
	1.3	0.1	2.7	1.7			2.507				
			3.9	2.3	2.633		1.622		0.6		
			5.5	3.1			1.103				
			7.8	4.3			0.745				
	1.4	0.2	2.6	0.65			0.143				
			3.8	0.85			0.091				
			5.8	1.15	0.275		0.059		1.6		
			8.4	1.55			0.04			0.8	
1.5	0.1	12.2	2.15			0.027					
		2.3	1.3			2.28					
		3.2	1.7	2.267		1.51		1.7			
		3.2	1.7			1.51					
Y CIM02	(3.5)	0.25	1.91	2.133	2.56	1.346	1.62		0.86		
			2.36	4.3	5.16	3.798	4.56	1.5	0.76		
			3.0	2.72	7.675	9.21	9.696	11.64		0.66	
			4.6	2.3	2.267		0.971		1.7	0.8	
	(5)	0.25	2.59	2.133	2.56	0.886	1.06		0.86		
			3.25	4.3	5.16	2.454	2.95	1.5	0.76		
			3.0	3.76	7.675	9.21	6.136	7.37		0.66	
			6.5	3.1	2.267		0.667		1.7	0.8	
	(7.5)	0.25	3.71	2.133	2.56	0.565	0.68		0.86		
			4.72	4.3	5.16	1.543	1.85	1.5	0.76		
			3.0	5.49	7.675	9.21	3.807	4.57		0.66	
			9.3	4.30	2.267		0.451		1.7	0.8	
	(10)	0.25	4.85	2.133	2.56	0.414	0.50		0.86		
			6.17	4.3	5.16	1.126	1.35		0.76		
			3.0	7.21	7.675	9.21	2.759	3.31		0.66	
			2.0	5.97	2.133	2.56	0.327	0.39		0.86	
	(12.5)	0.25	7.65	4.3	5.16	0.886	1.06		0.76		
			8.94	7.675	9.21	2.164	2.60		0.66		
			2.0	7.09	2.133	2.56	0.27	0.32		0.86	
			2.5	9.12	4.3	5.16	0.73	0.88		0.76	
	(15)	0.25	10.69	7.675	9.21	1.78	2.14		0.66		
			2.0	8.23	2.133	2.56	0.23	0.28		0.86	
			2.5	10.57	4.3	5.16	0.621	0.75		0.76	
			3.0	12.42	7.675	9.21	1.512	1.81		0.66	
1.8	0.2	3	1.3			0.962					
		4.4	1.7			0.612					
		6.4	2.3	1.642		0.396		2.1	1.1		
		9.2	3.1			0.269					
13.3	0.2	4.3				0.182					

① Y CIM02仅适用带()规格。

微型压缩弹簧

◀ 外径基准型

型号		d	压紧长度	压紧负荷(N)		弹簧常数(N/mm)		安装孔径	安装杆径	
代码	D			L	YCIM01	YCIM02	YCIM01			YCIM02
(2.9)	4.3		2.6			4.035	4.84	3.3	1.8	
	6.3		3.4			2.567	3.08			
	9.1	0.4	4.6	7.558	9.07	1.661	1.99			
	13		6.2			1.13	1.36			
	18.5		8.6			0.763	0.92			
(3)	7.5	0.25	2.08	1.792	2.15	0.331	0.4	3.12	2.29	
		0.3	2.69	3.117	3.74	0.649	0.78			
	10	0.25	2.59	1.792	2.15	0.242	0.29			2.29
		0.3	3.38	3.117	3.74	0.47	0.56			
	12.5	0.25	3.07	1.792	2.15	0.19	0.23			2.29
		0.3	4.06	3.117	3.74	0.369	0.44			
	15	0.25	3.58	1.792	2.15	0.157	0.19			2.29
		0.3	4.75	3.117	3.74	0.304	0.36			
	17.5	0.25	4.06	1.792	2.15	0.133	0.16			2.29
		0.3	5.41	3.117	3.74	0.258	0.31			
	20	0.25	4.57	1.792	2.15	0.116	0.14			2.29
		0.3	6.1	3.117	3.74	0.224	0.27			
	22.5	0.25	5.05	1.792	2.15	0.103	0.12			2.29
		0.3	6.78	3.117	3.74	0.198	0.24			
	25	0.25	5.56	1.792	2.15	0.092	0.11			2.29
		0.3	7.47	3.117	3.74	0.177	0.21			
	27.5	0.25	6.05	1.792	2.15	0.083	0.1			2.29
		0.3	8.13	3.117	3.74	0.161	0.19			
	30	0.25	6.55	1.792	2.15	0.076	0.09			2.29
		0.3	8.81	3.117	3.74	0.147	0.18			
(3.6)	5.6		2.6			1.924	2.31	4	2.5	
	8.3		3.4			1.224	1.47			
	12		4.6	6	7.2	0.792	0.95			
	17.5		6.2			0.539	0.65			
	25.5		8.6			0.364	0.44			
(4.4)	7.5		2.6			0.985	1.18	5	3.2	
	11		3.4			0.627	0.75			
	16.5	0.4	4.6	4.767	5.72	0.406	0.49			
	24		6.2			0.276	0.33			
	35.5		8.6			0.186	0.22			
(5.4)	10.5		2.6			0.504	0.61	6	4.1	
	16		3.4			0.321	0.39			
	24		4.6	4.042	4.85	0.208	0.25			
	35		6.2			0.141	0.17			
	53		8.6			0.095	0.11			

☐ YCIM02仅适用带()规格。



请按图示订货

型号			
代码	D	L	d
YCIM01	①	②	0.25
YCIM02	③	④	0.3

YCIM01—D3—L7.5—d0.25



未税价(元)

● 优惠价

数量	1~19	20~
价格	100%	另行报价



交货期

9