


塑料滑动轴承

高耐介质型 直柱型/肩型


代码	类型	材质	使用温度
OBE03	高耐介质型	直柱型	聚苯硫醚(PPS) 含润滑剂与特殊填充剂
OBE04		肩型	

- 特点: 自润滑, 免维护, 耐高温, 适合潮湿环境中使用。
- 用途: 广泛适用在潮湿和水下环境。
- 该产品为压配式衬套, 内径公差为压入座孔H7后公差, 压入后采用通止规进行测量(自由状态下请勿用卡尺进行测量)。
- 安装时保证H7座孔表面光滑、平整, 安装端倒角25°。禁止直接击打端面, 避免产品变形影响尺寸。

直柱型
OBE03



肩型
OBE04



推荐配套轴公差: h9



直柱型

型号	代码	d	d公差	L	D	a	b
OBE03	3	+0.046 +0.006	3 5	4.5			
	4		4 6	5.5			0.3
	5	+0.058 +0.010	5	7			
	6		4 6 10	8			
	8		5 8 10 15	10			
	10	+0.071 +0.013	6 10 12 15 20	12			0.5
	12		10 12 15 20	14			
	14		15 20 25	16			
	15	+0.086 +0.016	15 20 25	17		0.5	
	16		15 20 25	18			
	18		20 25 30	20			0.8
	20		15 20	23			
	25	+0.104 +0.020	20 25 30 40	28			
	30		20 30 50	34			
	35		20 40	39			
	40	+0.125 +0.025	20 50	44			1.2
	45		40	50			
	50			55			

肩型

型号	代码	d	d公差	L	D	H	T	b
OBE04	3	+0.046 +0.006	5	4.5	7.5	0.75		
	4		3 4 6	5.5	9.5			0.3
	5	+0.058 +0.010	5	7	11			
	6		4 6 10	8	12			
	8		5.5 7.5 10 15	10	15			
	10	+0.071 +0.013	5 9 10 12 15 17	12	18			0.5
	12		7 10 12 15 20	14	20	1		
	14		12	16	22			
	15	+0.086 +0.016	17	17	23			
	16		17	18	24			
	18		12 17	20	26			0.8
	20		11.5 16.5 21.5 30	23	30	1.5		
	25	+0.104 +0.020	30	28	35			
	30		40	34	42			
	35		26	39	47			
	40	+0.125 +0.025	40	44	52	2		1.2
	45		50	50	58			
	50		50	55	63			

直柱型

型号	代码	d	d公差	L
OBE04	3	+0.046 +0.006	3 4 6	
	4	+0.058 +0.010	5	

OBE04—d3—L5



优惠价
数量 1~9 10~
价格 100% 另行报价

未税价(元)



交货期
7



请按图示订货