



代码		螺纹	材质		硬度	表面处理
凹端	凸端		国标	相当		
TAY21	TAY31	粗牙	ML40Cr		45HRC~	发黑
TAY22	TAY32		0Cr18Ni9	SUS304	—	—

凹端
TAY21/22

① 适用标准: DIN 916-1980

凸端
TAY31/32

① 适用标准: DIN 915-1980

TAY21




TAY22



TAY31



TAY32



视角标准: 第一视角

凹端(ML40Cr)

代码	型号	M	L	S		d	
				Max	Min	Max	Min
TAY21	2	2		0.902	0.889	1	0.75
	3	3 4 5 6 8 10 12	16 20	1.545	1.52	1.4	1.15
	4	3 4 5 6 8 10 12	16 20 25	2.045	2.02	2	1.75
	5	4 5 6 8 10 12	16 20 25 30 35 40 45 50	2.56	2.52	2.5	2.25
	6	5 6 8 10 12	16 20 25 30 35 40 45 50 55 60 70	3.08	3.02	3	2.75
	8	6 8 10 12	16 20 25 30 35 40 45 50 55 60 65 70	4.095	4.02	5	4.7
	10	8 10 12	16 20 25 30 35 40 45 50 55 60 65 70 75 80 85 90 95 100	5.095	5.02	6	5.7
	12	10 12	16 20 25 30 35 40 45 50 55 60 65 70 75 80 90 100	6.095	6.02	8	7.64
	14		14 16 20 25 30 35 40 45 50 55 60 65	6.095	6.02	9	8.64
	16		16 20 25 30 35 40 45 50 55 60 65 70 75 80 90 100	8.115	8.025	10	9.64
	20		20 25 30 35 40 45 50 55 60 65 70 75 80 90 100	10.115	10.025	14	13.37

凹端(SUS304)

代码	型号	M	L	S		d	
				Max	Min	Max	Min
TAY22	2	2	2 3 4 5 6 8 10 12	0.902	0.889	1	0.75
	2.5	2.5	2.5 3 4 5 6 8	1.295	1.27	1.2	0.95
	3	3	3 4 5 6 8 10 12 16 20 25	1.545	1.52	1.4	1.15
	4	4	3 4 5 6 8 10 12 16 20 25 30	2.045	2.02	2	1.75
	5	5	3 4 5 6 8 10 12 16 20 25 30 35 40	2.56	2.52	2.5	2.25
	6	6	4 5 6 8 10 12 16 20 25 30 35 40 45 50	3.08	3.02	3	2.75
	8	8	5 6 8 10 12 16 20 25 30 35 40 45 50	4.095	4.02	5	4.7
	10	10	6 8 10 12 16 20 25 30 35 40 45 50	5.095	5.02	6	5.7
	12	12	8 10 12 16 20 25 30 35 40 45 50 55	6.095	6.02	8	7.64
	16	16	12 16 20 25 30 35 40 45 50	8.115	8.025	10	9.64

h尺寸表(TAY21/22)

M	2		2.5		3		4		5		6		8		10		12		14		16		20	
L	≤2.5	>2.5	≤3	>3	≤4	>4	≤5	>5	≤5	>5	≤6	>6	≤8	>8	≤10	>10	≤12	>12	≤14	>14	≤16	>16	≤20	>20
h(min)	0.8	1.7	1.2	2	1.2	2	1.5	2.5	2	3	2	3.5	3	5	4	6	4.8	8	5.6	9	6.4	10	8	12

凸端(ML40Cr/SUS304)

代码	型号	M	L	S		d	
				Max	Min	Max	Min
TAY31 TAY32	3	3	(3) 4 5 6 8 10 12	1.545	1.52	2	1.75
	4	4	4 5 6 8 10 12 16 20	2.045	2.02	2.5	2.25
	5	5	5 6 8 10 12 16 20 25 30	2.56	2.52	3.5	3.2
	6	6	6 8 10 12 16 20 25 30	3.08	3.02	4	3.7
	8	8	(6) 8 10 12 16 20 25 30	4.095	4.02	5.5	5.2
	10	10	10 12 16 20 25 30 35 (40) 45 50	5.095	5.02	7	6.64
	(12)	(12)	12 16 20 25 30 35 40 45 50	6.095	6.02	8.5	8.14

① 带()尺寸仅适用TAY31。

h/b尺寸表(TAY31/32)

M	3		4		5		6		8		10		12	
L	≤5	> 5	≤6	> 6	≤6	> 6	≤8	> 8	≤10	> 10	≤12	> 12	≤16	> 16
h(min)	1.2	2	1.5	2.5	2	3	2	3.5	3	5	4	6	4.8	8
b	0.75~1	1.5~1.75	1~1.25	2~2.25	1.25~1.5	2.5~2.75	1.5~1.75	3~3.25	2~2.25	4~4.3	2.5~2.75	5~5.3	3~3.25	6~6.3

凹端(SUS304)

代码	型号	M	L
TAY22	3	3	3 4 5 6 8 10
	4	4	3 4 5 6 8 10

TAY22—M4—L10



请按图示订货



未税价(元)

优惠价	数量	1~49	50~
价格	100%	另行报价	



交货期	3
-----	---