



线槽


PVC方形线槽 标准型

代码	类型	销售方式	材质	颜色	阻燃等级	温度
ZIK04	标准型	根	环保硬质PVC	灰色	UL94V-0	-20°C~+70°C
ZIK10		米				
ZIK09		盒				



特性：开口齿槽，反扣式槽盖与槽体设计组合后绝不脱落，且接合面平滑，不割伤手及擦损附近配线。



W ≤ 60mm 线槽底部孔尺寸



W ≥ 80mm 线槽底部孔尺寸



视角标准：第一视角

型号	W	A	销售方式：根 长度(米)	销售方式：米 起订数	销售方式：盒 包装方式(根/盒)	备注
代码	H		仅ZIK04	仅ZIK10	仅ZIK09	
ZIK04	20	20			130	
	25	20			110	
		25			90	
		30			100	
		35			80	
		40			70	
		45			60	
		50			50	若A尺寸为4， B尺寸则为6
		55			60	若A尺寸为6， B尺寸则为7
		60			50	若A尺寸为8， B尺寸则为10
		65			40	高度100及以上 A尺寸为10， B尺寸为10
		70			30	若有区别请以 实物尺寸为准
ZIK10	25	6	2	按2的倍数起订	60	
ZIK09	45	33	8			
ZIK04	45	45			50	
	50	50			40	
	55	55			36	
	60	60			24	
	65	65			20	
	70	70			16	
	75	75			12	
	80	80			10	
	85	85			8	
	90	90			6	
	95	95			4	
	100	100			3	

型号	W	A	销售方式：根 长度(米)	销售方式：米 起订数	销售方式：盒 包装方式(根/盒)	备注
代码	H		仅ZIK04	仅ZIK10	仅ZIK09	
ZIK04	45	45			40	
	50	50			36	
	55	55			30	
	60	60			20	
	65	65			18	
	70	70			12	
	75	75			10	
	80	80			8	
	85	85			6	
	90	90			4	
	95	95			3	
	100	100			2	
ZIK10	25	6	2	按2的倍数起订	60	
ZIK09	45	33	8			
ZIK04	45	45			40	
	50	50			36	
	55	55			30	
	60	60			20	
	65	65			18	
	70	70			12	
	75	75			10	
	80	80			8	
	85	85			6	
	90	90			4	
	95	95			3	
	100	100			2	



请按图示订货

型号	W	A
代码	H	
ZIK04	40	40
	50	25
		6

ZIK04—H40—W40—A4