



NXB-63小型断路器



◀ 3极/4极
正泰品牌

- 主要功能：过载、短路、隔离。
- 符合标准：GB/T10963.1, IEC60898-1。
- 符合认证：CCC、CE、SNI、EAC、TUV、Inmetro、SII、IRAM。
- 技术参数：
 - 额定电流：1A、2A、3A、4A、6A、10A、16A、20A、25A、32A、40A、50A、63A；
 - 额定电压：230V~(1P~2P), 400V~(2P~4P)；
 - 频率：50Hz；
 - 电磁脱扣器类型：C、D；
 - 极数：3P、4P；
 - 机械寿命：20000次；
 - 电气寿命：10000次；
 - 额定短路分断能力：6000A, 10000A(2P/230V)；
 - 运行短路分断能力：6000A, 7500A(2P/230V)；
 - 额定冲击耐受电压：4kV。



型号	额定电流(A)	极数	脱扣特性	额定电压	分断能力				
NXB-63 3P C1A	1	3P	C	230/400V AC	6KA				
NXB-63 3P C2A	2								
NXB-63 3P C3A	3								
NXB-63 3P C4A	4								
NXB-63 3P C6A	6								
NXB-63 3P C10A	10								
NXB-63 3P C16A	16								
NXB-63 3P C20A	20								
NXB-63 3P C25A	25								
NXB-63 3P C32A	32								
NXB-63 3P C40A	40								
NXB-63 3P C50A	50								
NXB-63 3P C63A	63								
NXB-63 3P D1A	1					4P	D	230/400V AC	6KA
NXB-63 3P D2A	2								
NXB-63 3P D3A	3								
NXB-63 3P D4A	4								
NXB-63 3P D6A	6								
NXB-63 3P D10A	10								
NXB-63 3P D16A	16								
NXB-63 3P D20A	20								
NXB-63 3P D25A	25								
NXB-63 3P D32A	32								
NXB-63 3P D40A	40								
NXB-63 3P D50A	50								
NXB-63 3P D63A	63								
NXB-63 4P C1A	1	4P	C	230/400V AC	6KA				
NXB-63 4P C2A	2								
NXB-63 4P C3A	3								
NXB-63 4P C4A	4								
NXB-63 4P C6A	6								
NXB-63 4P C10A	10								
NXB-63 4P C16A	16								
NXB-63 4P C20A	20								
NXB-63 4P C25A	25								
NXB-63 4P C32A	32								
NXB-63 4P C40A	40								
NXB-63 4P C50A	50								
NXB-63 4P C63A	63								
NXB-63 4P D1A	1					4P	D	230/400V AC	6KA
NXB-63 4P D2A	2								
NXB-63 4P D3A	3								
NXB-63 4P D4A	4								
NXB-63 4P D6A	6								
NXB-63 4P D10A	10								
NXB-63 4P D16A	16								
NXB-63 4P D20A	20								
NXB-63 4P D25A	25								
NXB-63 4P D32A	32								
NXB-63 4P D40A	40								
NXB-63 4P D50A	50								
NXB-63 4P D63A	63								

脱扣曲线图



型号
NXB-63 3P C6A
NXB-63 3P C10A

