



MUBEA 碟形弹簧

◀ 进口型

Mubea



视角标准：第一视角

代码	类型	材质	表面处理	最大压缩量
J-FEN03	碟形弹簧 进口型	51CrV4	锌磷化涂油	h×75%

厚度 t	荷重容许差 (75%位移量时)
< 1.25	-7.5% ~ +25%
1.25 ~ 3	-7.5% ~ +15%
> 3 ~ 6	-5.0% ~ +10%
> 6 ~ 15	±5%

① 荷重为参考值，非保证值，不作为判定依据。

代码	型号	厚度 t	全位移 (h)	总高度 L	压缩量 (F=h×75%) 时荷重
J-FEN03	8	0.3	0.25	0.55	104.3
		0.4	0.2	0.6	185.5
		0.5	0.2	0.7	357.4
		0.3	0.25	0.55	117.9
		0.4	0.2	0.6	209.5
		0.5	0.3	0.7	379.1
	10	0.3	0.35	0.65	98.3
		0.4	0.3	0.7	179.1
		0.5	0.35	0.85	404
		0.4	0.3	0.7	189.1
		0.6	0.25	0.85	502.3
		0.4	0.3	0.7	209.3
	12	0.5	0.25	0.75	325.3
		0.4		0.8	178.3
		0.5	0.4	0.9	331.4
		0.6		1	556.8
			0.95		506.1
		0.5	0.35	0.85	326.4
	12.5	0.6		0.95	551.7
		0.35	0.45	0.8	151.2
		0.5	0.35	0.85	293.4
		0.4	0.4	0.9	279.2
		0.8	0.3	1.1	796.8
		0.4	0.55	0.95	175.5
	14	0.5	0.5	1	278.2
		0.7	0.55	1.25	796.5
		0.5	0.5	1	289.4
		0.7		1.1	577.5
		0.8	0.4	1.2	982.3
		0.4	0.5	0.9	154.3
	16	0.6	0.45	1.05	410
		0.9	0.35	1.25	1013
		0.5		1.1	245.4
		0.6	0.6	1.2	400.3
		0.8	0.7		1072
		1	0.5	1.5	1497
	18	0.45	0.6	1.05	213.7
		0.7	0.5	1.2	566.4
		1	0.4	1.4	1254

代码	型号	厚度 t	全位移 (h)	总高度 L	压缩量 (F=h×75%) 时荷重
J-FEN03	20	0.5	0.65	1.15	230.8
		0.6	0.7	1.3	412
		0.7	0.65	1.35	568.5
		0.8		1.4	751
		0.9	0.6	1.5	1051
		1		1.6	1424
	22.5	0.4	0.5	0.9	98.5
		0.5	0.65	1.15	254.1
		0.8		1.35	748.2
		0.9	0.55	1.45	1050
		1		1.55	1425
		1.1	0.45		1521
	23	0.6	0.8	1.4	425.4
		0.8	0.65	1.45	707.4
		1.25	0.5	1.75	1929
		0.8	0.75	1.55	718.5
		0.9	0.8	1.7	1078
		0.75	1.65	1.05	1058
	25	1	0.7	1.7	1315
				1.6	1217
		1.25	0.6	1.85	2331
		1.5		2.1	3986
		0.7	0.9	1.6	599.6
		0.9	0.7		862.3
	28	1.5	0.55	2.05	2926
		0.8	0.95	1.75	661.5
		1.5	0.7	2.2	2723
		1	0.95	1.95	1268
		1.25	0.85	2.1	2083
		1.5	0.75	2.25	3077
	31.5	0.8	1	1.8	801.4
		1	0.8		1107
		1.25	0.85	2.1	2240
		1.5	0.65	2.15	2841
		1.25	0.9		1913
		1.5	2.4		3230
	31.5	1.75	0.7	2.45	3871
		2	0.75	2.75	6173

型号				厚度 t	全位移 (h)	总高度 L	压缩量 (F=h×75%) 时荷重
代码	D	d					
J-FEN03	34	12.3		1.25	1.2	2.45	1110
				1.5		2.7	3363
		14.3		1.25	1.15	2.4	1993
				1.5	1.05	2.55	2990
	35.5	16.3		1.25	1	2.25	1699
				2		0.8	2.8
		18.3		1.25	1.4	2.65	1780
				1.5	1.3	2.8	2668
	40	16.3		2	1.05	3.05	4769
				1.5	1.3	2.8	2749
		18.3		1.75	1.35	3.1	4435
				2	1.15	3.15	5656
	45	20.4		1.5		2.65	2621
				2	1.1	3.1	5701
		22.4		2.25	0.9	3.15	6500
				2.5	0.95	3.45	9390
	48	16.3		1.25	1.6	2.85	1891
				1.75	1.3	3.05	3646
		25.4		2.5	1	3.5	7716
				1.5	1.5	3	2195
	50	18.4		1.25	1.6	2.85	1375
				2	3.65	5114	
		20.4		2.5	1.65	4.15	9643
				3	1.2	4.2	11630
56	22.4		2	1.5	3.5	4687	
			2.5	1.4	3.9	8510	
	25.4		1.25	1.6	2.85	1550	
			1.5		3.1	2512	
60	25.4		2	3.4	4.762	4762	
			2.5	3.9	9063	9063	
	30.5		3	1.1	4.1	11976	
			1.5	1.95	3.45	2622	
63	28.5		2.5	1.7	4.2	8978	
			3	1.3	4.3	11388	
	31		2	4.2	5.026	5026	
			2.5	2.2	4.7	9255	
70	20.5		3	5.2	15465	15465	
			2.5	1.9	4.4	8175	
	25.5		3	1.65	4.65	11784	
			2.5	4.5	9432	9432	
71	30.5		2.75	2	4.75	12356	
			3	1.7	4.7	13226	
	35.5		3.5	1.5	5	18153	
			1.8	2.35	4.15	4238	
80	31		2.5	1.75	4.25	7189	
			3	1.7	4.7	11772	
	35.5		3.5	1.4	4.9	15025	
			3	2.3	5.3	12007	
88	24.5		3.5	2.5	6	20495	
			2	4.5	5.1	4437	
	30.5		2.5	2.4	4.9	8031	
			3	2.1	5.1	11426	



请按图示订货

代码	D	d	厚度 t
J-FEN03	8	0.15	0.3

J-FEN03—D8—d3.2—t0.3



优惠价

数量	1~4	5~
价格	100%	另行报价

未税价(元)



交货期

8