


特软硅胶线

代码	类型	导体	绝缘材质	温度范围
ZIF03	耐高温线	镀锡铜线	硅胶	-60°C~+200°C

☑ 适用

- 适用于电动模型，航模，电池，配电柜，机器人等长期工作，环境温度为-60°C~+200°C范围内使用。



销售方式	每卷长度
卷	见参数表



代码	型号		颜色	长度(m)	截面积 (mm ²)	导体结构 (根/mm)	绝缘厚度 (mm)	绝缘外径 (mm)	额定电压 (V)		
	导体AWG										
ZIF03	30		R(红色) BK(黑色)		0.05	11/0.08	0.4	1.2	600		
	28				0.08	16/0.08		1.3			
	26				300	0.15		30/0.08		1.5	
	24				(300米整卷销售)	0.2		40/0.08		1.6	
	22					0.3		60/0.08		1.7	
	20				200	0.5		100/0.08		1.8	
	18					0.75		150/0.08		2.3	
	16					1.25		252/0.08		3.0	
	15					1.5		300/0.08		3.2	
	14					2		400/0.08		3.5	
	13					2.5		500/0.08		3.8	
	12					3.4		680/0.08		4.5	
	11					3.8		750/0.08		5.0	
	10					5.2		1050/0.08		5.4	
	9				100	6.5		1300/0.08		5.7	
	8					8.3		1650/0.08		6.0	
	7					(100米整卷销售)		10.5		2100/0.08	7.5
	6					16		3200/0.08		8.5	
	5					17		3400/0.08		8.7	
	4					21.6		4300/0.08		9.0	
2			33.6	6700/0.08	12.5						
1/0		50	53	10640/0.08	2.4	15.8					
		(50米整卷销售)									



请按图示订货

型号		颜色	长度(m)
代码	导体AWG		
ZIF03	30	R(红色)	300
	28	BK(黑色)	(300米整卷销售)

ZIF03-30-R-300

