


常规型


代码	系列	类型	端子类型
ZID31	Z系列	弹片式接线型	常规型

Weidmüller


CQC CE




规格: 252/252B




规格: 253/253B




规格: 2541/2541B




规格: 254/254B





规格: 255/255B



规格: 42/42B



规格: 62



视角标准: 第一视角


型号 代码	规格	导线最大 压接面积(mm ²)	通道数	层数	厚度	颜色	额定电压(V)				额定电流(A)				额定截面积(mm ²)				
							IEC	UL	CSA	EN50019	IEC	UL	CSA	EN50019	IEC	UL	CSA	EN50019	
ZID31	252	2.5	2	1	5.1	深灰色	800	600	600	550	24	25	27	21	2.5	2.5			
	蓝色					800	600	600	550	24	25	27	21	2.5					
	253		3	1		5.1	深灰色	800	600	600	550	24	25	27	21	2.5	AWG26~12	2.5	
	蓝色						800	600	600	550	24	25	27	21	2.5	AWG26~12	2.5		
	2541		4	2		5.1	深灰色	800	600	600	550	24	25	27	21	2.5	2.5		
	蓝色						800	600	600	550	24	25	27	21	2.5				
	254		4	2		1	6.1	深灰色	500	300	300	275	20	10	10	18	2.5	AWG26~14	2.5
	蓝色							500	300	300	275	20	10	10	18	2.5	AWG26~14	2.5	
	255		4	2		1	6.1	深灰色	500	300	300	440	20	10	10	20	2.5	AWG26~12	2.5
	蓝色							500	300	300	440	20	10	10	20	2.5	AWG26~12	2.5	
42	4	2	1	6.1	深灰色	800	600	600	550	32	33	35	28	4	AWG26~10	4			
42B	4	2	1	6.1	深灰色	800	600	600	550	32	33	35	28	4	AWG26~10	4			
62	6	2	1	8	深灰色	800	600	600	550	41	45	50	36	6	22~8 20~8	6			

接地型


代码	系列	类型	端子类型
ZID47	Z系列	弹片式接线型	接地型

Weidmüller


CQC CE




规格: 25




规格: 253




规格: 2541




规格: 254



规格: 40



规格: 62



视角标准: 第一视角

型号 代码	规格	导线最大 压接面积(mm ²)	通道数	层数	厚度	颜色	额定电压(V)				额定短时 电流(A)	额定截面积(mm ²)					
							IEC	UL	CSA	EN50019	IEC	UL	CSA	EN50019			
ZID47	25	2.5	2	1	5.1	绿色	800	800	800	800	300	AWG26~12					
	253						800	800	800	550	300	2.5	AWG30~12	AWG26~12	2.5		
	2541		4	2			1	6.1	500	500	500	500	—	AWG26~14 AWG26~12			
	254								800	800	800	800	480	4	AWG26~10		
	40		4	2			1	6.1	800	800	800	800	480	4	AWG26~10		
62	6	2	1	8.1	800	800	800	800	480	6	AWG22~8	AWG20~8	6				



型号	代码	规格	导线最大 压接面积(mm ²)
ZID47	25	254	2.5

请按图示订货 ZID47—25

接线端子