

代码	类型	材质	表面处理
TCJ04	W型	碳钢	
TCJ03		合金钢	热浸锌处理
TCJ06		碳钢	
TCJ07	X型	S45C	镀蓝白锌

特点:

- 弓形卸扣均采用锻造碳钢，且配置螺栓；
- 弓形卸扣制造过程中经100%磁力探伤裂纹测试；
- 以1.5倍工作荷载极的作用力进行20000次的疲劳极限测试。

TCJ04




TCJ03





TCJ06



W型
TCJ04/03



X型
TCJ06/07



视角标准：第一视角

W型

代码	型号	规格	工作载荷极限(吨)	安全系数	B	D	W	A	E	G	H	净重(kg)
TCJ04		0.5T	0.5	6	6.35	7.85	11.9	28.7	19.8	15.5	46.7	0.05
		0.75T	0.75		7.85	9.65	13.5	31	21.3	19.1	53	0.09
		1T	1		9.65	11.2	16.8	36.6	26.2	23.1	63	0.14
		1.5T	1.5		11.2	12.7	19.1	42.9	29.5	26.9	74	0.17
		2T	2		12.7	16.0	20.6	47.8	33.3	30.2	83.5	0.33
		3.25T	3.25		16.0	19.1	26.9	60.5	42.9	38.1	106	0.62
		4.75T	4.75		19.1	22.4	31.8	71.5	51	46	126	1.07
		6.5T	6.5		22.4	25.4	36.6	84	58	53	148	1.64
8.5T	8.5	25.4	28.7	42.9	95.5	68.5	60.5	167	2.28			

W型(合金钢)

代码	型号	规格	工作载荷极限(吨)	安全系数	B	D	W	A	E	G	H	净重(Kg)
TCJ03		1.2T	1.2	5.4	8	9.5	12	31	21	19	54	0.1
		2T	2		10	11	16	36	26	23	65	0.1
		2.7T	2.6		11	13	19	43	30	27	75	0.2
		3.3T	3.4		13	16	20	47	33	30	85	0.3
		5T	5		16	19	27	61	45	39	107	0.6

X型(碳钢)

代码	型号	规格	工作载荷极限(吨)	安全系数	B	D	W	A	E	G	H	净重(kg)
TCJ06		0.5T	0.5	6	6.35	7.85	11.9	28.7	19.8	15.5	46.7	0.05
		0.75T	0.75		7.85	9.65	13.5	31	21.3	19.1	53	0.1
		1T	1		9.65	11.2	16.8	36.6	26.2	23.1	63	0.15
		1.5T	1.5		11.2	12.7	19.1	42.9	29.5	26.9	74	0.22
		2T	2		12.7	16	20.6	47.8	33.3	30.2	83.5	0.36
		3.25T	3.25		16	19.1	26.9	60.5	42.9	38.1	106	0.62
		4.75T	4.75		19.1	22.4	31.8	71.5	51	46	126	1.23
		6.5T	6.5		22.4	25.4	36.6	84	58	53	148	1.79
8.5T	8.5	25.4	28.7	42.9	95.5	68.5	60.5	167	2.28			

X型(S45C)

型号		工作载荷极限(吨)	安全系数	B	D	W	A	E	G	H	净重(kg)
代码	规格										
TCJ07	0.5T	0.5	6	6.35	7.87	11.94	28.7	19.81	15.49	46.74	0.08
	0.75T	0.75		7.874	9.65	13.46	30.99	21.34	19.05	53.09	0.1
	1T	1		9.65	11.18	16.76	36.58	26.16	23.11	63.25	0.15
	1.5T	1.5		11.18	12.7	19.05	42.93	29.46	26.92	73.91	0.22
	2T	2		12.7	16	20.57	47.75	33.27	30.23	83.31	0.36
	3.25T	3.25		16	19.05	26.92	60.45	42.93	38.1	106.43	0.76
	4.75T	4.75		19.05	22.35	31.75	71.37	50.8	45.97	126.24	1.23
	6.5T	6.5		22.35	25.4	36.58	84.07	57.91	53.09	148.08	1.79
	8.5T	8.5		25.4	28.7	42.93	95.25	68.33	60.45	166.62	2.78
	9.5T	9.5		28.70	31.75	45.97	107.95	73.91	68.33	189.74	3.75
	12T	12		31.75	35.05	51.56	119.13	82.55	76.2	209.55	5.31
	13.5T	13.5		35.05	38.1	57.15	133.35	92.2	84.07	232.66	7.18
	17T	17		38.1	41.4	60.45	146.05	98.55	92.2	254	9.43
	25T	25		44.45	50.8	73.15	177.8	127	106.43	313.44	15.38
	35T	35		52.83	58.42	82.55	196.85	146.05	122.17	347.47	23.7
	55T	55		68.83	71.12	104.9	266.7	184.15	144.53	454.66	44.57
85T	85	79.25	83.82	127	330.2	200.15	165.1	546.1	69.85		
120T	120	91.95	95.5	133.35	371.6	228.6	203.2	631.95	120.2		



请按图示订货

型号		工作载荷极限(吨)
代码	规格	
TCJ07	0.5T	0.5
	0.75T	0.75

TCJ07—0.5T



未税价(元)

优惠价

数量	1~499	500~
价格	100%	另行报价



交货期

7

怡合达
AUTOMATION EXPERT 自动化专家

怡合达
AUTOMATION EXPERT 自动化专家