


推力滚针轴承


代码	类型			材质
BKL	标准型	单件	带保持器止推滚针	SUJ2
BNL			止推圈	65Mn
BBL		套件	带保持器止推滚针+止推圈	SUJ2+65Mn




单件
带保持器止推滚针
BKL



止推圈
BNL



组件
带保持器止推滚针+止推圈
BBL



止推圈在交货时可能会有少许变形，使用前请以同心圆的方式施加最低200N轴向负载即可使之平整。



型号		带保持器止推滚珠						止推圈×2			极限转速	基本额定负载(KN)		参考重量(g)					
代码	轴承型号	d	D	A	E	E ₁	d ₁	D ₁	B	(rpm)	Cr(动)	Cor(静)	BKL	BNL	BBL				
BKL BNL BBL	0414	4	14	-0.095			13	5	4	14	-0.032	15050	3.08	5.6	0.7	1	2.7		
	0515	5	+0.140 +0.020	15	-0.365		14	6	5	+0.200 +0.020	15	14420	3.325	6.44	0.8	1	2.8		
	0619	6	19				18	7	6	19		13230	4.76	10.85	1	2	5		
	0821	8	+0.175 +0.025	21			20	9	8	+0.245 +0.025	21	12460	5.46	13.58	2	2	6		
	1024	10	24	-0.11 -0.44			23	12	10	24	-0.040 -0.370	11830	6.44	17.85		3			
	1226	12	26				25	14	12	26		10640	6.93	20.3	3	3	9		
	1528	15	+0.212 +0.032	28			27	17	15	+0.302 +0.032	28	9240	7.91	25.2	4	3	10		
	1730	17	30				29	19	17	30		8470	8.33	27.65	4	4	12		
	2035	20	35	-0.12 -0.51			34	22	20	35		7350	9.17	32.55	5	5	15		
	2542	25	+0.250 +0.004	42	-0.13 -0.52		41	29	25	+0.370 +0.040	42	5880	10.29	40.6	7	7	21		
	3047	30	47				46	34	30	47		5110	11.41	49	8	8	24		
	3552	35	52				51	39	35	52		4550	12.46	56.7	10	9	28		
	4060	40	60	-0.14 -0.60			58	45	40	60		3920	19.6	79.8	16	12	40		
	4565	45	65				63	50	45	+0.44 +0.05	65	3570	21	89.6	18	13	44		
	5070	50	70	-0.15 -0.61			68	55	50	70		3290	22.4	100.1	20	14	48		
	5578	55	78			3	0 -0.01	76	60	55	78	1	±0.05	2980	26.6	130.2	28	18	64
	6085	60	85				83	65	60	85		2730	31.15	163.8	33	22	77		
	6590	65	90				88	70	65	90		2560	39.76		35	24	83		
	7095	70	+0.36 +0.06	95	-0.17 -0.71			93	74	70	+0.52 +0.06	95	2420	37.8	178.5	60	25	110	
	75100	75	100				98	79	75	100	-0.072 -0.612	2280	38.5	185.5	61	27	115		
	80105	80	105				103	84	80	105		2170	39.2	196	63	28	119		
	85110	85	110	-0.18 -0.72			108	89	85	110		2070	40.6	203	67	29	125		
	90120	90	120			4		118	94	90	120		1890	51.1	283.5	86	39	164	
	100135	100	+0.422 +0.072	135	-0.20 -0.83			133	105	100	+0.612 +0.072	135	1690	63.7	392	104	50	204	
	110145	110	145				143	115	110	145		1560	67.9	434	122	55	232		
	120155	120	155	-0.21 -0.84			153	125	120	155	-0.085 -0.715	1450	71.4	476	131	59	249		
	130170	130	170	-0.23 -0.86			167	136	130	170		1330	93.1	588	205	65	335		
	140180	140	180				177	146	140	180	+0.715 +0.085	1250	96.6	630	219	79	377		
	150190	150	190	+0.485 +0.085			187	156	150	190		1180	100.1	672	232	84	400		
	160200	160	200	-0.24 -0.96			197	166	160	200	-0.10 -0.82	1110	103.6	714	246	89	424		

d4~d8规格为尼龙保持架，d8以上规格为钢制保持架。

1Kg=9.81N



型号		
代码	轴承型号	d
BKL	0414	4
BNL	0515	5

BKL0414



数量	1~9	10~
价格	100%	另行报价

未税价(元)



交货期
5