


代码	类型	销售方式	材质	硬度
UEN21B	尺寸选择型	袋装	SUS304H	350~400HV
UEN26B			黄铜(C2801P或C2680P)	—

① 1袋30个装。



6.3



T公差表

代码	T公差									
	0.01	0.02	0.03	0.05	0.1	0.2	0.3	0.5	0.8	1.0
UEN21B	±0.003	±0.003	±0.005	±0.005	±0.02	±0.03	±0.035	±0.04	±0.04	±0.05
UEN26B	—	—	—	—	—	—	±0.04	±0.05	—	±0.08



视角标准：第一视角

型号		D																T	
代码	d																		
UEN21B	(2)	3																(0.01) 仅UEN21B	
		4 5 6																	
	3	4																	
		5 6 7 8 10																	
	4	6 7 8 10 12																	
	5	7 8 10 12 14 16																	
	6	8 10 12 14 16																	
	8	12 14 16 18 20																	
	10	12 14 16 18 20																	
	12	16 18 20 21 22																	
	(15)	18 20 21 22 24																	
	(17)	20 21 22 24 28 30 32																	
	(20)	24 28 30 32 35 40																	
	(22)	28 30 32																	
UEN26B	(25)	30 32 35 40 42																	
	(30)	35 40 42 45 50																	
	(35)	42 45 50 55																	
	(40)	45 50 55																	
	(45)	50 55																	

(0.01)
仅UEN21B0.05
0.1
0.2
0.3
0.5
1.0

① 带 () d尺寸不适用UEN26B。

① 当d=2, D=3时, 不适用UEN26B。

① 当d=2, D=3时, 厚度T0.5、T1.0不适用UEN21B。

① 当d=3, D=4时, 厚度T0.5、T1.0不适用UEN21B。

① 当d=3, D=4时, 不适用UEN26B。



请按图示订货

型号		D	T
代码	d		
UEN21B	3	4	0.1
	5 6 7	0.2	

UEN21B—d3—D5—T0.2



未税价(元)

● 优惠价

数量	1~499	500~999	1000~
价格	100%	95%	另行报价



交货期

5