


代码	类型	材质	硬度	表面处理
TAS11	E型	弹簧钢	44~53HRC	ACP(磷酸盐皮膜)
TAS12		SUS304	37~46HRC	—



□ 本产品适用标准: JIS B 2804-2001

视角标准: 第一视角

● 弹簧钢

型号	挡圈								适用轴(参考)						
	代码	规格	内径d		外径D		H	t	d ₁		d ₂	m	n(min)		
			大于	以下											
TAS11	1.2	1.2	3	±0.1	1	0.3	±0.025	1.4	2	1.23	0.4	0.6			
	1.5	1.5	4		1.3			2	2.5	1.53		0.8			
	1.9	1.9	4.5		1.7			2.5	3	1.93					
	2	2	5		1.7	0	0.4	±0.03	2.5	3.2	2.05	+0.05	0.5		
	2.3	2.3	6		2	-0.25			3	4	2.35	0	1		
	2.5	2.5	6		2.1				3.2	4	2.55				
	3	3	7		2.6				4	5	3.05				
	3.2	3.2	7		2.8				4	5	3.25				
	4	4	9	±0.2	3.5		0.6		5	7	4.05	+0.075			
	5	5	11		4.3	0	-0.3		6	8	5.05	0	+0.01	1.2	
	6	6	12		5.2			±0.04	7	9	6.05				
	7	7	14		6.1				8	11	7.1			1.5	
	8	8	16		6.9		0.8		9	12	8.1	+0.09	0.9	1.8	
	9	9	18		7.8	0	-0.35		10	14	9.1	0		2	
	10	10	20		8.7				11	15	10.15			1.15	
	12	12	23		10.4		1	±0.05	13	18	12.15	+0.11		2.5	
15	15	29	±0.3	13	0	-0.45		16	24	15.15	0	+0.14	3		
19	19	37		16.5		1.5	±0.06	20	31	19.15	+0.13	0	3.5		
24	24	44		20.8	0	-0.5	±0.07	25	38	24.15	0		4		

● SUS304

型号	挡圈								适用轴(参考)						
	代码	规格	内径d		外径D		H	t	d ₁		d ₂	m	n(min)		
			大于	以下											
TAS12	0.8	0.8	2	±0.1	0.7	0.2	±0.02	1	1.4	0.8	+0.05	0.3	0.4		
	1.2	1.2	3		1			0.3	±0.025	1.4	2	1.2	0.6		
	1.5	1.5	4		1.3					2	2.5	1.5	+0.05	0.8	
	2	2	5		1.7	0	-0.25	0.4	±0.04	2.5	3.2	2	+0.06	0.5	
	2.5	2.5	6		2.1					3.2	4	2.5		1	
	3	3	7		2.6					4	5	3			
	4	4	9	±0.2	3.5		0.6			5	7	4		0.7	
	5	5	11		4.3	0	-0.3			6	8	5	+0.075		
	6	6	12		5.2			±0.03		7	9	6		+0.1	1.2
	7	7	14		6.1					8	11	7			1.5
	8	8	16		6.9		0.8			9	12	8	+0.09	0.9	1.8
	9	9	18		7.8	0	-0.35			10	14	9	0		2
	10	10	20		8.7					11	15	10			1.15
	12	12	23		10.4		1	±0.05		13	18	12	+0.11		2.5
	15	15	29	±0.3	13	0	-0.45			16	24	15	0	+0.14	3
	19	19	37		16.5		1.5	±0.06		20	31	19	+0.13	0	3.5
24	24	44		20.8	0	-0.5	±0.07		25	38	24	0		4	

● 弹簧钢

代码	规格
(TAS11)	1.2
(TAS12)	1.5

TAS11—1.5

● SUS304

代码	规格
(TAS12)	0.8
(TAS12)	1.2

TAS12—1.2

● 优惠价
数量 1~99 100~
价格 100% 另行报价

未税价(元)

交货期
7

垫圈·吊环
螺母·螺帽
C2