

标准型·安装孔通孔
加长型·安装孔通孔

法兰型导向轴支座

标准型·安装孔通孔

标准型・安装孔通孔			材质		表面处理	
圆法兰型	方法兰型	对边法兰型	国标	相当		
GAC01	GAC11	GAC21	45	S45C	发黑	
GAC02	GAC12	GAC22			喷细砂无电解镀镍	
GAC06	GAC16	GAC26	0Cr18Ni9	SUS304	喷细砂本色阳极氧化 黑色阳极氧化	
GAC08	GAC18	GAC28	LD30	A6061		
GAC09	GAC19	GAC29				







① 如对防锈有要求, 请优先选用不锈钢材质、铝合金材质或喷细砂无电解镍产品。

圆法兰型
GAC01/02/06/08/09

方法兰型
GAC11/12/16/18/19

对边法兰型
GAC21/22/26/28/29



视角标准: 第一视角

代码	型号	L	D1	H	T	V	P.C.D	K	W	P	F	d1	M
圆法兰型	3	10	7.8	22	3		15	16	8	15			
GAC01	4	12	8.8	24		8	17	19	9	17			
GAC02	5	15	9.8	25	3.5		18	20	10	18		3.5	M3
GAC06	6	16	11.8	28		11	20	22	16	20			
GAC08	8											4.5	M4
GAC09	8M				5							3.5	M3
方法兰型	10	20	13.8	30		13	22	23	18	22			
GAC11	10M												
GAC12	12	24	15.8	36		16	26	28	20	26			
GAC16	13		17.8	38	6		28	30	22	28		4.5	M4
GAC18	15	30	19.8	40		19	30	32	24	30			
GAC19	16		21.8	42		20	32	33	26	28	16		
对边法兰型	18	32	27.8	50	8	21	39	39	32	31	22	5.5	M5
GAC21	20												
GAC22	25	38	32.8	55		24	44	44	37	36	24		
GAC26	30		37.8	66		25	52	52	42	41	27	6.6	
GAC28	35		44.8	80			65	65	55	56	33		
GAC29	40	50	59.8	90	10	32	75	75	65	65	38	9.0	M6
	50		69.8	100			85	90	75	74	43		

加长型·安装孔通孔

加长型·安装孔通孔			材质		表面处理
圆法兰型	方法兰型	对边法兰型	国标	相当	
GAJ01	GAJ11	GAJ21	45	S45C	发黑
GAJ02	GAJ12	GAJ22			喷细砂无电解镍
GAJ06	GAJ16	GAJ26	0Cr18Ni9	SUS304	



① 如对防锈有要求, 请优先选用不锈钢材质或喷细砂无电解镍产品。







D12

D16~30

圆法兰型
GAJ01/02/06

方法兰型
GAJ11/12/16

对边法兰型
GAJ21/22/26



视角标准: 第一视角

代码	型号	L	D1	H	T	V	P.C.D	K	W	P	F	d1	M
圆法兰型	12	30	15.8	36	6	16	26	28	20	26		4.5	M4
方法兰型	16	48	21.8	42		17	32	33	26	28	16		
GAJ01	16		27.8	50	8		39	39	32	31	22	5.5	M5
GAJ02	20		32.8	55		20	44	44	37	36	24		
GAJ06	25	57	37.8	66	10		52	52	42	41	27	6.6	M6
	30												



请按图示订货

代码	型号	DH7
GAC01	8	+0.015
GAC02	8M	0
GAC02	8M	0



未税价(元)

● 优惠价

数量	1~9	10~
价格	100%	另行报价



交货期

5