

成对双联角接触球轴承


组合型 · DB/DF配对 · 无密封圈
进口型 接触角25°




代码	类型	轴承类型 代码	轴承精度	轴承材质		接触角 (°)
				国标	相当	
BBQ...-J	组合型	进口型	7	JIS B 1514 0级	GCr15 SUJ2	25

① 出厂前未封入润滑脂，请在使用前封入。


-DB(反面)




■ 安装图



-DF(正面)



■ 安装图



型号		组合形式	d	D	B	r (min)	r ₁ (min)	基本额定负载 (kN)		容许转速rpm (参考)		作用点a		安装尺寸						重量 kg (参考)	
代码	轴承型号							Cr(动)	Cor(静)	脂润滑	油润滑	DB	DF	d ₀ (min)	d _a (max)	r _a (max)	d _b (min)	d _a (max)	r _a (max)		
BBQ...-J	7000	DB (反面)	10	26	8	0.3	0.15	8.75	5.2	20000	28000	18.4	2.2	12.5	24.8	0.3	11.2	23.5	0.15	0.02	
	7200			30	9	0.6	0.3	8.8	5.4				20.5	2.8	15	27.5	0.6	12.5	25	0.3	0.03
	7001		12	28	8	0.3	0.15	9.4	5.95	18000	24000	19.5	3.9	14.5	26.8	0.3	13.2	25.5	0.15	0.02	
	7201			32	10	0.6	0.3	13	8.05	16000		22.7	2.7	17	29.5	0.6	14.5	27	0.3	0.04	
	7002		15	9	0.3	0.15	9.95	6.85	15000		22.6	4.6	17.5	30.8	0.3	16.2	29.5	0.15	0.03		
	7202			35	11	0.6	0.3	14	9.3		20000	25.4	3.7	20	32.5	0.6	17.5	30	0.3	0.05	
	7003		17	10	0.3	0.15	10.4	7.65	14000	19000	25.0	5.3	19.5	33.8	0.3	18.2	32.5	0.15	0.04		
	7203			40	12	0.6	0.3	17.6	12	13000	17000	28.5	4.8	22	37.5		19.5	35			
	7004		DF (正面)	20	42	12	0.6	0.3		13.2	12000	16000	29.9	6.2	25	39.5	0.6	22.5	37	0.3	0.07
	7204				47	14	1	0.6	23.5	16.6	11000	15000	33.3	5.9	26	42	1	25	41	0.6	0.11
	7005	25		12	0.6	0.3	18.3	14.8	10000	14000	32.8	8.9	30	44.5	0.6	27.5	42	0.3	0.08		
	7205			52	15			26.3	20.5	9500	13000	37.2	7.5	31	47		30	46			
	7006	30		55	13	1		23.6	20.2	8500	12000	37.5	11.5		50		49	0.6	0.12		
	7206			62	16			36.5	29.5	8000	11000	42.6	11		36		57	35			
	(7207)	1.1		0.6	35	72	17		48.5	40	6700	9500	47.9		42	67	1				0.29
	(7208)				40	80	18		57.5	50.5	6000	8500	52.6		47	75					0.38
	(7209)		45		85	19		64.5	57.5	5600	7500	56.5		52	80					0.41	
	(7210)		50		90	20		67	63	5000	7100	60.4		57	85					0.47	

① 带 () 规格无DF(正面)组合形式。

① 1Kg=9.81N



请按图示订货

型号	组合形式
代码 轴承型号	
BBQ...J	7000 DB
	7200 DF
BBQ7000DB-J	



未税价(元)

● 优惠价

数量	1~9	10~
价格	100%	另行报价



交货期

5