



代码	类型		材质	表面处理
EUX21	法兰型	带定心功能	S45C	—
EUX22				喷砂镀镍


※拆卸用螺孔



推荐安装尺寸：

轴：h8
毂：H8

类似JB/T7934 Z8型免键胀套



视角标准：第一视角

※拆卸用螺孔的螺径与锁紧螺栓相同。

型号		D	D ₁	L ₁	L ₂	L ₃	L	传递的 轴向力	传递 扭矩	接触面压强		DIN912-12.9级锁紧螺钉		
代码	d									轴	毂	数量	规格	锁紧扭矩
EUX21 EUX22	19								243	234				
	20	47	56					26	256	222	94	5		
	22								282	202				
	24	50	59						368	222	106			
	25								383	213				
	28	55	64	17	22	28	34	31	429	190	97	6	M6×20	17
	30								460	177				
	32	60	69						655	222	118			
	35							41	716	203		8		
	38	65	74						778	187	109			
	40								819	178				
	42	75	84						1361	227	127			
	45							65	1458	212	127	7		
	50	80	89						1620	191	119			
	55	85	94	20	25	33	41		2037	199	129	8	M8×25	41
60	90	99					74	2223	182	121				
65	95	104					83	2710	189	129	9			
70	110	119						4203	211	134				
75	115	124	24	30	40	50	120	4754	197	128	8	M10×30	83	
80	120	129						4804	184	123				



请按图示订货

型号		D
代码	d	
EUX21	19	47
EUX22	20	
	22	
EUX21—d19		



未税价(元)

优惠价

数量	1~4	5~
价格	100%	另行报价



交货期

5



Example
使用示例

