

ISO标准矩形弹簧



超重载荷弹簧(黄色)

代码	类型	材质	最大压缩量
YSIB	超重载型	SWOSC-V	L×25%

□ L尺寸公差

L	公差
89以下	±1
102以上	±1%

- ① 载荷(±10%)
- ① 直角度(3°以下)
- ① 负载(N)=弹簧常数(N/mm)×压缩量
- ① 理论使用次数: 30万次(L×17%为100万次)
- ① 弹簧颜色和圈数可能会因生产批次不同而异, 但产品性能均符合标准, 不影响使用!
- ① 参考标准 ISO 10243-2019



型号		轴径 D _d	弹簧常数 N/mm	使用方法 30万次 F=L×25%		
代码	孔径D			长度L	Fmm	负载N
YSIB	10	5	25	36.8	6.2	228.2
			32	27.9	8	223.2
			38	23.7	9.5	225.2
			44	19.2	11	211.2
			51	16.5	12.7	209.6
			64	13.2	16	211.2
			76	10.9	19	207.1
			305	2.6	76.3	198.4
	12.5	6.3	25	58.5	6.2	362.7
			32	43.9	8	351.2
			38	36	9.5	342
			44	30.3	11	333.3
			51	26.2	12.7	332.7
			64	21.2	16	339.2
			76	17.1	19	324.9
			89	14.5	22.2	321.9
	16	8	305	4.3	76.3	328.1
			25	118	6.2	731.6
			32	89	8	712
			38	72.1	9.5	685
			44	60.9	11	669.9
			51	52.3	12.7	664.2
			64	41.2	16	659.2
			76	34.1	19	647.9
	20	10	89	29.5	22.2	654.9
			102	25.6	25.5	652.8
			305	8.4	76.3	640.9
			25	293	6.2	1817
			32	224	8	1792
			38	177	9.5	1682
			44	149	11	1639
			51	128	12.7	1626
	25	12.5	64	99	16	1584
			76	81.7	19	1552
			89	69.5	22.2	1543
			102	60.6	25.5	1545
			115	53	28.7	1521
			127	47.5	31.7	1506
			139	43	34.7	1492
			152	39	38	1482
	305	20	305	20	76.3	1526
			32	374	8	2992
			38	300	9.5	2850
			44	244	11	2684
			51	208	12.7	2642
			64	161	16	2576
			76	131	19	2489
			89	111	22.2	2464

型号		轴径 D _d	弹簧常数 N/mm	使用方法 30万次 F=L×25%		
代码	孔径D			长度L	Fmm	负载N
YSIB	25	12.5	102	96.3	25.5	2456
			115	85.7	28.7	2460
			127	76.3	31.7	2419
			139	66	34.7	2290
			152	63.5	38	2413
			178	53.9	44.5	2399
			203	47	50.7	2383
			305	30.9	76.3	2358
	32	16	38	480	9.5	4560
			44	390	11	4290
			51	336	12.7	4267
			64	269	16	4304
			76	219	19	4161
			89	180	22.2	3996
			102	155	25.5	3953
			115	140	28.7	4018
	40	20	127	124	31.7	3931
			139	112	34.7	3886
			152	102	38	3876
			178	88.2	44.5	3925
			203	76	50.7	3853
			254	60.8	64	3891
			305	49	76.3	3739
			51	628	12.7	7976
	50	25	64	487	16	7792
			76	379	19	7201
			89	321	22.2	7126
			102	281	25.5	7166
			115	245	28.7	7032
			127	221	31.7	7006
			139	185	34.7	6420
			152	168	38	6384
	305	25	178	150	44.5	6675
			203	132	50.7	6692
			254	107	64	6848
			305	87.8	76.6	6725
			64	709	16	11344
			76	572	19	10868
			89	475	22.2	10545
			102	405	25.5	10328
	305	25	115	352	28.7	10102
			127	316	31.7	10017
			139	289	34.7	10028
			152	255	38	9690
			178	215	44.5	9568
			203	187	50.7	9481
			254	153	64	9792
			305	127	76.3	9690

弹簧
氮气
弹簧
C4



型号		
代码	孔径D	长度L
YSIB	10	25
		32



● 优惠价	数量 1~9	10~
	价格 100%	另行报价

交货期	7
-----	---