



无油垫片/止推垫片



无油垫片·铜合金

代码	类型	材质
OFU01	锥孔型	高力黄铜(SP2)
OFU02	沉孔型	镶嵌固体润滑剂


锥孔型(内六角沉头螺钉用)
OFU01



沉孔型(内六角薄圆柱头螺钉用)
OFU02



视角标准：第一视角





型号	代码	规格	T	D	D1	P.C.D	数量	安装孔	OFU01	OFU02	倒角
锥孔型 OFU01	6			6.2	25	15		M3	3.5	6	2.4
	8			8.2	28	18					
	10			10.2	30	20					
	12	3(4)		12.2	40	28					
	13			13.2							
	15			15.2							
	16			16.2							
	18			18.2							
	20			20.2							
	25			25.2							
沉孔型 OFU02	30	5		30.2	60	45		M5	4.5	7.5	3
	35			35.2	70	50					
	40			40.2	80	60					
	50	7		50.3	100	75					
	6			6.2	25	15		M6	5.5	9	4
	8			8.2	28	18					
	10			10.2	30	20					
	12	3(4)		12.2	40	28					
	13			13.2							
	15			15.2							
	16			16.2							
	18			18.2							
	20			20.2							
	25			25.2							

OFU02 规格6~18的T尺寸为 () 内的尺寸。 螺钉需另行采购。

无油垫片·工程塑料

代码	类型	材质	耐热温度
OFU03	无孔型	工程塑料	-40~80℃

- 自润滑、高耐磨、耐脏污、耐灰尘。适用高强度震动和灰尘环境中。
- 安装在两工件之间，防止工件对磨产生粘连。



视角标准：第一视角



型号	代码	d	D	t
OFU03	6	6	9	0.6

请按图示订货 OFU03—d5—D9—t0.6



优惠价
数量 1~1000 1001~
价格 100% 另行报价



8

型号	代码	d	D	t
OFU03	5	9	0.6	
	6	15	1.5	
	20			
	15	0.5		
	8	1.5		
	1			
	18	1.5		
	1			




型号	代码	d	D	t
OFU03	10	18	1.5	
	2			
	12	24		
	26	1.5		
	14	30		
	24			

型号	代码	d	D	t
OFU03	16	30		
	32	1.5		
	18	36		
	28	3		
	30			
	36	1.5		
	20	38		

型号	代码	d	D	t
OFU03	22	38		
	42			
	24	44		
	26	48		
	28	54		
	30			
	32			

止推垫片

代码	类型	基板	中间层	表面层	表面处理	耐热温度
OFW01	止推垫片	SPCC	青铜粉	聚四氟乙烯 (PTFE)	镀锡	-200~280℃



视角标准：第一视角

型号	代码	规格	t	d	D	安装孔	d1	P.C.D
OFW01	6			8	16	1.0		12
	8			10	18			14
	10			12	24	1.5		18
	12			14	26			20
	14			16	30	2.0		23
	16			18	32			25
	18	1.5		20	36			28
	20			22	38	3.0		30
	22			24	42			33
	25			28	48			38
	30			32	54			43
	35			38	62	4.0		50
	40			42	66			54
	50	2.0		52	78			65



型号	代码	规格	t
OFW01	6		1.5

请按图示订货 OFW01—6



优惠价
数量 1~9 10~
价格 100% 另行报价



5