



免键胀套

直杆短型

代码	类型	材质	表面处理
EUX66	直杆短型	S45C	—
EUX67			喷砂镀镍

拆卸用螺栓和锁紧用螺栓重合



视角标准：第一视角

型号		D	H	P.C.D	H ₁	H ₂	锁紧螺栓				容许最大扭矩(N·m)	容许轴向负载(KN)	重量(g)
代码	d						M×L	个数	内六角扳手公称尺寸	紧固扭矩(N·m)			
EUX66 EUX67	20	47		34.5				8			300	29.5	240
	22			34.5					330	230			
	24	50		37.5				9			410	33.8	250
	25			37.5					430	240			
	28	55	26	42.5	20	17	M6×L18	10	5	12.7	530	37.8	290
	30												570
	32	60		47.5				12			730	45.4	340
	35			47.5					800	310			
	38	65		52.5				14			1010	52.9	370
	40			52.5					1060	350			
	42	75		60				12			1560	74.1	600
	45			60					1670	570			
	48	80		65				14			1780	91.8	630
	50		32	24	20	M8×L22		6	29.4	1860	610		
	55	85			70				14			2530	
	60	90		75							2760		700
	65	95		80					16			2990	



请按图示订货

型号		D	H
代码	d	47	26
EUX66	22	47	
EUX67	24	50	

EUX66—d24



未税价(元)

● 优惠价

数量	1~4	5~
价格	100%	另行报价



交货期

5

● 轴及轮孔部的推荐公差、表面粗糙度

安装面	公差	表面粗糙度
轴外径	h7(g6)	Ra1.6以下
孔轮部内径	H7	Ra3.2以下