

聚氨酯减震材料

代码





来图定制



NBF55/52/51/53/54
NBF61/62/63/64/65/66

L	G
$30 < L-H$	$G \leq D-4$
$30 \geq L-H$	$G \leq D-5$




 视角标准：第一视角

尺寸	公差		
	V	H	G
30以下	±0.20	±0.20	±0.20
31~90	±0.30	±0.50	±0.30
91~200	—	±0.50	—

尺寸	V	H·G
2~50	±0.14	±0.09
51~	±0.14	±0.14

型号		最小单位1	最小单位0.5			
代码		D	V	H	G	L
普通级	精密级	8~15	2~12			
NBF05 NBF11	NBF55 NBF61	16~30	2~18	H=3~L		6.0~80
NBF02 NBF12	NBF52 NBF62					
NBF01 NBF13	NBF51 NBF63	31~45	5~40			8.0~150
NBF03 NBF14	NBF53 NBF64	46~60	5~50		3~90	20.0~150
NBF04 NBF15	NBF54 NBF65	61~80	5~70	H=2~L		
NBF16	NBF66	81~100	5~84			20.0~200



型号	最小单位1	最小单位0.5			
代码	D	V	H	G	L
NBF01	8~15	2~12	H=3~L	3~90	6.0~80
NBF02					

请按图示订货 NBF01-D10-V4-H6-G6-L50




未税价(元)

数量	1~9	10~
价格	100%	另行报价



7

代码	类型		材质	硬度	颜色
NBF06	普通级	沉孔型	高回弹 聚氨酯	肖氏A95	蓝色



视角标准：第一视

型号		L	d ₁	d ₂	安装 螺栓	F=L×10%		F=L×15%		F=L×20%		
代码	D					F	负载 N(kgf)	F	负载 N(kgf)	F	负载 N(kgf)	E
NBF06	20	20				2.0		3.0		4.0		
		25				2.5	2886 (294)	3.7	3469 (354)	5.0	4086 (417)	23.9
		30				3.0		4.5		6.0		
	25	25	11	6.5	M6	2.5		3.7		5.0		
		30				3.0	5305	4.5	6381	6.0	7475	29.9
		35				3.5	(541)	5.2	(650)	7.0	(762)	
		40				4.0		6.0		8.0		
		30	30				3.0		4.5		6.0	
	35		14	9	M8	3.5	7475 (762)	5.2	8959 (913)	7.0	10476 (1068)	36
	40					4.0		6.0		8.0		

⚠ kgf = N × 0.101972



型号		L
代码	D	
NBF06	20	20
		25

请按图示订货 NBF06—D20—L20



未税价(元)

数量	1~9	10~
价格	100%	另行报价



7