



P尺寸指定型		材质		硬度	表面处理
Dm6	Dp6	国标	相当		
YGP81	YGP91			淬火硬度58~61HRC	—
YGP82	YGP92	9CrWMn	SKS3	淬火硬度58~61HRC, 镀层硬度850HV~	镀硬铬, 镀层厚度3~5μm
YGP83	YGP93			—	—
YGP88	YGP98	0Cr18Ni9	SUS304	镀层硬度850HV~	镀硬铬, 镀层厚度5~8μm
YGP89	YGP99			—	—
YGP86	YGP96	9Cr18Mo	SUS440C	淬火硬度48~53HRC	—



◎ P尺寸公差表

P	h6
1.50~3	<sup>0</sup> <sub>-0.006</sub>
3.01~6	<sup>0</sup> <sub>-0.008</sub>
6.01~10	<sup>0</sup> <sub>-0.009</sub>
10.01~18	<sup>0</sup> <sub>-0.011</sub>
18.01~20	<sup>0</sup> <sub>-0.013</sub>



型号		D公差			最小单位0.01	L	B	V	C
代码		m6	p6	P					
Dm6 Dp6 YGP81 YGP91 YGP82 YGP92 YGP83 YGP93 YGP88 YGP98 YGP89 YGP99 YGP86 YGP96	2			1.50~2.00	4		0	0.1	
	3	+0.008 +0.002	+0.012 +0.006	1.50~3.00	5	3			
	4			2.00~4.00	8		1	0.5	
	5	+0.012 +0.004	+0.020 +0.012	2.00~5.00	10	4			
	6			2.00~6.00	12				
	8	+0.015 +0.006	+0.024 +0.015	3.00~8.00	16	5		1	
	10			3.00~10.00	20	6	2	1.5	
	12	+0.018 +0.007	+0.029 +0.018	5.00~12.00	22	10		2	
	13			6.00~13.00	30	20		3	
	16	+0.021 +0.008	+0.035 +0.022	10.00~16.00					
	20			13.00~20.00					



请按图示订货

型号	D	P	L
YGP81	2	1.50~2.00	4
YGP82	3	1.50~3.00	5

YGP81—D2—P2

◎ 可选加工

型号	D	P	可选加工代码
YGP81	16	10.00~16.00	RC CN
YGP82	20	13.00~20.00	

YGP81—D16—P16—CN



未税价(元)

● 优惠价

数量	1~4	5~
价格	100%	另行报价



交货期

8



可选加工

代码	技术说明
RC	<p>变更颈部退刀槽为R0.5</p> <p>【选型方法】 RC □ D-P &lt; 2时, 不适用</p>

代码	技术说明
CN	<p>变更倒角C</p> <p>【选型方法】 CN 变更P尺寸部的倒角为C0.5以下 □ D≤3时, 不适用 □ 仅适用P尺寸部</p>