


代码				螺纹	材质		硬度	表面处理
平端	锥端	凹端	凸端		国标	相当		
TAY01	TAY11	TAY21	TAY31	粗牙	ML40Cr	45HRC~	发黑	
TAY02	TAY12	TAY22	TAY32		0Cr18Ni9	SUS304		—

※当M与L相等时, 锥端(TAY11、TAY12)尾部角度为60°。




平端
TAY01/02




适用标准: DIN 913-1980

锥端
TAY11/12




适用标准: DIN 914-1980

凹端
TAY21/22



适用标准: DIN 916-1980

凸端
TAY31/32



适用标准: DIN 915-1980

平端(ML40Cr)

型号	代码	M	L	S	h	d
TAY01	2	2 3 4 5		0.9	0.8	1
	2.5	3 4 5 6 8		1.3	1.2	1.5
	3	3 4 5 6 8 10 12 16 20		1.5	1.2	2
	4	3 4 5 6 8 10 12 16 20		2	1.5	2.5
	5	4 5 6 8 10 12 16 20 25 30		2.5	2	3.5
	6	5 6 8 10 12 16 20 25 30 35 40 45 50		3	2	4
	8	6 8 10 12 16 20 25 30 35 40 45 50		4	3	5.5
	10	8 10 12 16 20 25 30 35 40 45 50		5	4	7
	12	10 12 16 20 25 30 35 40 45 50 60 70		6	4.8	8
16	16 20 25 30 35 40 45 50 60 70		8	6.4	12	

锥端(ML40Cr)

型号	代码	M	L	S	h	d
TAY11	3	3 4 5 6 8 10 12 20		1.5	1.2	—
	4	4 5 6 8 10 12 16		2	1.5	—
	5	5 6 8 10 12 16 20		2.5	2	—
	6	6 8 10 12 16 20 25 30 35 40		3	2	1.5
	8	8 10 12 16 20 25 30		4	3	2
	10	10 12 16 20 25 30		5	4	2.5
	12	12 16 20 25 30 35 40		6	4.8	3
16	16 20 25 30 35 40 45 50		8	6.4	3.5	

平端(SUS304)

型号	代码	M	L	S	h	d
TAY02	2	2 3 4 5 6 8 10 12		0.8	0.8	1
	2.5	2.5 3 4 5 6 8 10 12		1.2	1.2	1
	3	3 4 5 6 8 10 12 16 20 25		1.5	1.2	2
	4	3 4 5 6 8 10 12 16 20 25 30 35 40		2	1.5	2.5
	5	3 4 5 6 8 10 12 14 16 20 25 30 35 40		2.5	2	3.5
	6	4 5 6 8 10 12 16 20 25 30 35 40 45 50		3	2	4
	8	5 6 8 10 12 16 20 25 30 35 40 45 50 60		4	3	5.5
	10	6 8 10 12 16 20 25 30 35 40 45 50 55 60		5	4	7
	12	8 10 12 16 20 25 30 35 40 45 50 55		6	4.8	8
16	12 16 20 25 30 35 40 45 50		8	6.4	12	

锥端(SUS304)

型号	代码	M	L	S	h	d
TAY12	2	3 4 5 6 8 10 12 16		0.9	0.8	—
	2.5	3 4 5 6 8 10 12 16		1.3	1.2	—
	3	3 5 6 8 10 12 16 20		1.5	1.2	—
	4	3 4 5 6 8 10 12 16 20 25 30		2	1.5	—
	5	4 5 6 8 10 12 16 20 25 30 35 40		2.5	2	—
	6	4 5 6 8 10 12 16 20 25 30 35 40 45 50		3	2	1.5
	8	6 8 10 12 16 20 25 30 35 40 45 50		4	3	2
	10	8 10 12 16 20 25 30 35 40 45 50		5	4	2.5
	12	10 12 16 20 25 30 35 40 45 50		6	4.8	3
	16	16 20 25 30 35 40 45 50		8	6.4	3.5

凹端(ML40Cr)

型号	代码	M	L	S	h	d
TAY21	3	3 4 5 6 8 10 12 16 20		1.5	1.2	1.4
	4	3 4 5 6 8 10 12 16 20 25		2	1.5	2
	5	4 5 6 8 10 12 16 20 25 30 35 40 45 50		2.5	2	2.5
	6	5 6 8 10 12 16 20 25 30 35 40 45 50 55 60 70		3	2	3
	8	6 8 10 12 16 20 25 30 35 40 45 50 55 60 65 70		4	3	5.5
	10	8 10 12 16 20 25 30 35 40 45 50 55 60 65 70 75 80 85 90 95 100		5	4	6
	12	10 12 16 20 25 30 35 40 45 50 55 60 65 70 75 80 90 100		6	4.8	8
	14	14 16 20 25 30 35 40 45 50 55 60 65		6	5.6	9
	16	16 20 25 30 35 40 45 50 55 60 65 70 75 80 90 100		8	6.4	10
	20	20 25 30 35 40 45 50 55 60 65 70 75 80 90 100		10	7.2	12

凹端(SUS304)

型号	代码	M	L	S	h	d
TAY22	2	2 3 4 5 6 8 10 12		0.9	0.8	1
	2.5	2.5 3 4 5 6 8		1.3	1.2	1.2
	3	3 4 5 6 8 10 12 16 20 25		1.5	1.2	1.4
	4	3 4 5 6 8 10 12 16 20 25 30		2	1.5	2
	5	3 4 5 6 8 10 12 16 20 25 30 35 40		2.5	2	2.5
	6	4 5 6 8 10 12 16 20 25 30 35 40 45 50		3	2	3
	8	5 6 8 10 12 16 20 25 30 35 40 45 50		4	3	5
	10	6 8 10 12 16 20 25 30 35 40 45 50		5	4	6
	12	8 10 12 16 20 25 30 35 40 45 50 55		6	4.8	8
16	12 16 20 25 30 35 40 45 50		8	6.4	10	

凸端(ML40Cr/SUS304)

型号	代码	M	L	S	h	d	b
TAY31 TAY32	3	(3) 4 5 6 8 10 12		1.5	1.2	1.75	0.75
	4	4 5 6 8 10 12 16 20		2	1.5	2.25	1
	5	5 6 8 10 12 16 20 25 30		2.5	2	3.2	1.25
	6	6 8 10 12 16 20 25 30		3	2	3.7	1.5
	8	(6) 8 10 12 16 20 25 30		4	3	5.2	2
	10	10 12 16 20 25 30 35 (40) 45 50		5	4	6.64	2.5
	(12)	12 16 20 25 30 35 40 45 50		6	4.8	8.14	3

带()尺寸仅适用TAY31。



平端

型号	代码	M	L	S
TAY01	3	3 4 5 6 8 10	1.5	
TAY01-M4-L10	4	3 4 5 6 8 10	2	



优惠价

数量	1~49	50~
价格	100% 另行报价	

