

精密型真空吸盘用金属支架

顶部真空端口 带缓冲型

| 代码 | 类型 | 缓冲形式 |
|---------|--------|------|
| J-WEY21 | 顶部真空端口 | 可回转 |
| J-WEY22 | | 不可回转 |


特点:

- 实现低摩擦、低噪音、噪音级45dB;
- 采用无铜材质, 防摩擦, 减少粉尘掉落;
- 设有防止偏心结构, 上下动作顺滑。


J-WEY21

规格: 8/10

行程: 5/10/15




规格: 10
行程: 3




EX

Example
使用示例




规格: 10F
行程: 3




EX

Example
使用示例



J-WEY22



视角标准: 第一视角

| 型号 | | 缓冲行程 | 缓冲形式 | M | A | B | C | E | H | S | M ₁ |
|---------|----|---------|------|---------|------|------|----|-----|-----|----|----------------|
| 代码 | 规格 | | | | | | | | | | |
| J-WEY21 | 8 | 5 | 可回转 | M8×0.7 | 43 | 5.5 | 25 | 7.5 | 3 | 10 | M4×0.7 |
| | | 10 | | | 48 | 10.5 | | | | | |
| | | 3 | | | 16.5 | 5.5 | | | | | |
| | 10 | 5 | | M10×1.0 | 48 | 5 | 34 | 4 | 3.5 | 13 | M5×0.8 |
| | | 10 | | | 53 | 10 | | | | | |
| | | 15 | | | 58 | 15 | | | | | |
| 10F | 3 | M10×1.0 | 20.5 | 5.5 | 11.5 | — | — | | | | |

| 型号 | | 缓冲行程 | 真空端 连接螺纹 | 缓冲形式 | M | M ₁ | A | B | C | S | | |
|---------|----|------|-------------|---------|--------|----------------|----|------|------|------|----|------|
| 代码 | 规格 | | | | | | | | | | | |
| J-WEY22 | 10 | 5 | 不可回转 | M10×1.0 | M5×0.8 | 40 | 5 | 24.5 | 29.5 | 13 | | |
| | | 10 | | | | | | | | | 50 | 10 |
| | | 15 | | | | | | | | | 60 | 15 |
| | 14 | 5 | | M14×1.0 | M6×1.0 | 52.5 | 10 | 31.5 | 17 | | | |
| | | 10 | | | | | | | | 42.5 | 5 | 26.5 |
| | | 15 | | | | | | | | 62.5 | 15 | 36.5 |



| 型号 | | 缓冲行程 |
|---------|----|------|
| 代码 | 规格 | |
| J-WEY21 | 8 | 5 |
| | 10 | 3 |

J-WEY21-10-3



| ● 优惠价 | |
|-------|-----------|
| 数量 | 1~9 10~ |
| 价格 | 100% 另行报价 |



| |
|---|
| 9 |
|---|