


代码	类型	材质	使用温度
OBE05	高化学抗性型	工程塑料	-100°C ~ +250°C
OBE06			


- 特点: 自润滑, 免维护, 耐高温, 高温高载荷下耐磨性较好, 化学抗性优异。
- 用途: 广泛温度应用范围和高压敏感性特点。



直柱型  
OBE05



肩型  
OBE06



推荐配套轴公差: h9

视角标准: 第一视角

### 直柱型

型号		d公差	L	D	a	b
代码	d					
OBE05	3	+0.046 +0.006	5 6	4.5	0.3	
	4		4 6	5.5		
	5	+0.058 +0.010	5 8 10	7		
	6		4 6 8 10 15	8		
	8	+0.071	5 8 10 12 15	10	0.5	
	10	+0.013	6 8 10 12 15 20	12		
	12		6 8 10 12 15 20 25	14		
	14		8 10 12 15 20 25	16		
	15	+0.086 +0.016	8 10 15 20	17	0.5	
	16		8 10 12 15 20 25	18		
	18		15 20 25	20		
	20		10 15 20 25 30	23		
	25	+0.104 +0.020	12 15 20 25 30	28	1.2	
	30		20 25 30 40	34		
	35		20 25 30 40 50	39		
	40	+0.125 +0.025	20 30 40 50	44		
45		30	50	1.2		
50		40 50	55			

### 肩型

型号		d公差	L	D	H	T	b
代码	d						
OBE06	3	+0.046 +0.006	5	4.5	7.5	0.75	0.3
	4		3 4 6	5.5	9.5		
	5	+0.058 +0.010	4 5	7	11		
	6		4 6 8 10	8	12		
	8	+0.071	4 5.5 7.5 10 15	10	15	1	0.5
	10	+0.013	5 6 7 8 9 10 12 15 17	12	18		
	12		5 6 7 10 12 15 17 20	14	20		
	14		10 12 17	16	22		
	15	+0.086 +0.016	5 9 12 17 20	17	23	1.5	0.8
	16		6 9 12 17 20 25	18	24		
	18		9 12 17	20	26		
	20		7 11.5 16.5 21.5	23	30		
	25	+0.104 +0.020	11.5 16.5 21.5	28	35	2	1.2
	30		16 26 37	34	42		
	35		9 16 26	39	47		
	40	+0.125 +0.025	14 30 40 50	44	52		
45		50	50	58	1.2		
50		40	55	63			

### 直柱型

型号		d公差	L
代码	d		
OBE05	3	+0.046 +0.006	5 6
	4	+0.058 +0.010	4 6

OBE05—d3—L5



未税价(元)

### 优惠价

数量	1~9	10~
价格	100%	另行报价



### 交货期

7



请按图示订货