



防水型 圆形连接器

◀ 方形法兰插座 SA系列 威浦品牌


WEIPU® 威浦电器



系列	类型	接插方式	材质			防护等级
			外壳	绝缘体	接触件	
SA系列	方形法兰插座	推入式快速锁紧	铝 (阳极氧化)	热塑塑料PPS	铜(镀金)	IP67 (连接后)



安装开孔尺寸



尺寸表

系列	D ₂	L	L ₁	D ₁	A	B	K	D
SA12	11.9	20	13	13.8	18	13	2.3	12
SA16	15.8	22.1	13.1	18.3	26	20	3.2	16
SA20	19.8	23.3	14.4	21.6	29	22	3.2	20
SA24	23.8	24	—	25.3	32	26	3.2	24
SA28	27.8	23.3	14	29.8	37	30	3.2	28



视角标准：第一视角

插针

型号	颜色	配合直径	芯数	适配插头	
				电缆插头	
SA1213P2		12	2	SA1210S2	
SA1213P3			3	SA1210S3	
SA1213P4			4	SA1210S4	
SA1213P5			5	SA1210S5	
SA1213P6			6	SA1210S6	
SA1213P7			7	SA1210S7	
SA1213P9			9	SA1210S9	
SA1613P2			16	2	SA1610S2
SA1613P3				3	SA1610S3
SA1613P4		4		SA1610S4	
SA1613P5		5		SA1610S5	
SA1613P7		7		SA1610S7	
SA1613P9		9		SA1610S9	
SA1613P10		10		SA1610S10	
SA2013P2		20		2	SA2010S2
SA2013P3				3	SA2010S3
SA2013P4			4	SA2010S4	
SA2013P5			5	SA2010S5	
SA2013P6			6	SA2010S6	
SA2013P7			7	SA2010S7	
SA2013P8			8	SA2010S8	
SA2013P9			9	SA2010S9	
SA2013P12	B(黑色) S(银色)		12	SA2010S12	
SA2013P15		15	SA2010S15		
SA2413P2		24	2	SA2410S2	
SA2413P3			3	SA2410S3	
SA2413P4			4	SA2410S4	
SA2413P9			9	SA2410S9	
SA2413P10			10	SA2410S10	
SA2413P12			12	SA2410S12	
SA2413P19			19	SA2410S19	
SA2813P2			28	2	SA2810S2
SA2813P3				3	SA2810S3
SA2813P4		4		SA2810S4	
SA2813P7		7		SA2810S7	
SA2813P8		8		SA2810S8	
SA2813P9		9		SA2810S9	
SA2813P10		10		SA2810S10	
SA2813P12		12		SA2810S12	
SA2813P16		16		SA2810S16	
SA2813P17		17		SA2810S17	
SA2813P20		20		SA2810S20	
SA2813P24		24		SA2810S24	
SA2813P26		26		SA2810S26	
SA2813P35		35		SA2810S35	

插孔

型号	颜色	配合直径	芯数	适配插头	
				电缆插头	
SA1213S2		12	2	SA1210P2	
SA1213S3			3	SA1210P3	
SA1213S4			4	SA1210P4	
SA1213S5			5	SA1210P5	
SA1213S6			6	SA1210P6	
SA1213S7			7	SA1210P7	
SA1213S9			9	SA1210P9	
SA1613S2			16	2	SA1610P2
SA1613S3				3	SA1610P3
SA1613S4		4		SA1610P4	
SA1613S5		5		SA1610P5	
SA1613S7		7		SA1610P7	
SA1613S9		9		SA1610P9	
SA1613S10		10		SA1610P10	
SA2013S2		20		2	SA2010P2
SA2013S3				3	SA2010P3
SA2013S4			4	SA2010P4	
SA2013S5			5	SA2010P5	
SA2013S6			6	SA2010P6	
SA2013S7			7	SA2010P7	
SA2013S8			8	SA2010P8	
SA2013S9			9	SA2010P9	
SA2013S12	B(黑色) S(银色)		12	SA2010P12	
SA2013S15		15	SA2010P15		
SA2413S2		24	2	SA2410P2	
SA2413S3			3	SA2410P3	
SA2413S4			4	SA2410P4	
SA2413S9			9	SA2410P9	
SA2413S10			10	SA2410P10	
SA2413S12			12	SA2410P12	
SA2413S19			19	SA2410P19	
SA2813S2			28	2	SA2810P2
SA2813S3				3	SA2810P3
SA2813S4		4		SA2810P4	
SA2813S7		7		SA2810P7	
SA2813S8		8		SA2810P8	
SA2813S9		9		SA2810P9	
SA2813S10		10		SA2810P10	
SA2813S12		12		SA2810P12	
SA2813S16		16		SA2810P16	
SA2813S17		17		SA2810P17	
SA2813S20		20		SA2810P20	
SA2813S24		24		SA2810P24	
SA2813S26		26		SA2810P26	
SA2813S35		35		SA2810P35	

技术参数

接插方式	推入式快速锁紧
接线方式	焊接
接插次数	500次
温度范围	-40°C~+85°C



型号	颜色
SA1213P2	黑色
SA1213P4	银色

请按图示订货 SA1213P2-B