




膜片式联轴器

◀ 螺钉夹紧型

不锈钢 单膜片/双膜片

代码	类型	材质		表面处理	附件
		主体	膜片	主体	
DBM31	螺钉夹紧型	不锈钢	不锈钢	—	内六角圆柱头螺钉
DBM41					

单膜片
DBM31双膜片
DBM41

视角标准：第一视角

型号		d-e																											
代码	D																												
单膜片 DBM31	15	d	3		4		5																						
		e	3 4 5		4 5		5																						
	19	d	4		5		6		8																				
		e	4 5 6 8		5 6 8		6 8		8																				
	25	d	5			6			8		10		11		12														
		e	5 6 8 10 11 12			6 8 10 11 12			8 10 11 12		10 11 12		11 12		12														
27	d	6			8			10		11		12		14															
	e	6 8 10 11 12 14			8 10 11 12 14			10 11 12 14		11 12 14		12 14		14															
34	d	6				8				10				11		12		14		15		16							
	e	6 8 10 11 12 14 15 16				8 10 11 12 14 15 16				10 11 12 14 15 16				11 12 14 15 16		12 14 15 16		14 15 16		15 16		16							
双膜片 DBM41	39	d	8				10				11		12		14		15		16		18		19		20				
		e	8 10 11 12 14 15 16 18 19 20				10 11 12 14 15 16 18 19 20				11 12 14 15 16 18 19 20		12 14 15 16 18 19 20		14 15 16 18 19 20		15 16 18 19 20		16 18 19 20		18 19 20		19 20		20				
	44	d	8				10				11		12		14		15		16		18		19		20		22		
		e	8 10 11 12 14 15 16 18 19 20 22				10 11 12 14 15 16 18 19 20 22				11 12 14 15 16 18 19 20 22		12 14 15 16 18 19 20 22		14 15 16 18 19 20 22		15 16 18 19 20 22		16 18 19 20 22		18 19 20 22		19 20 22		20 22		22		
	56	d	10				11				12				14				15				16						
		e	10 11 12 14 15 16 18 19 20 22 24 25 28				11 12 14 15 16 18 19 20 22 24 25 28				12 14 15 16 18 19 20 22 24 25 28				14 15 16 18 19 20 22 24 25 28				15 16 18 19 20 22 24 25 28				16 18 19 20 22 24 25 28						
d		18				19				20				22				24				25				28			
e		18 19 20 22 24 25 28				19 20 22 24 25 28				20 22 24 25 28				22 24 25 28				24 25 28				25 28				28			

型号		L	L1	L2	d1	F	A	M	锁紧扭矩 (N·m)	额定扭矩 (N·m)	最大扭矩 (N·m)	最高转速 (r/min)	惯性力矩 (kg·m²)	静态扭转刚度 (Nm/rad)	容许安装偏差			重量(g)
代码	D														径向(mm)	角向(°)	轴向(mm)	
单膜片 DBM31	15	16.7	7.5			2.3	5.25	M2	0.5	0.5	1	42000	2.3×10 ⁻⁷	500	0.02	0.5	±0.1	15
	19	19.7	9			2.5	7.1		1	2	2	33000	7.4×10 ⁻⁷	1000				29
	25	23.8	11			3.5	9.25	M2.5	1	1.2	2.4	25000	2.8×10 ⁻⁵	1500				53
	27	23.8	11				10.25		1.5	3	3	23000	3.8×10 ⁻⁵	2100				67
	34	26.2	12			4	13	M3	1.5	3.5	7	18000	1.1×10 ⁻⁵	3800				115
	39	33.1	15			5	14.5	M4	3.5	5	10	16000	2.3×10 ⁻⁵	5500				185
双膜片 DBM41	44	33.1	15			17			7	14	14	14000	3.9×10 ⁻⁵	7000	0.05	1	±0.3	305
	56	43.5	20			6	21.25	M5	8	15	30	11000	1.4×10 ⁻⁴	15000				610
	15	23.4	7.5	5	5.1	2.3	5.25	M2	0.5	0.5	1	42000	5.0×10 ⁻⁷	300				20
	19	26.9	9	5.5	8.5	2.5	7.1		1	2	2	33000	1.6×10 ⁻⁵	550				38
	25	32.6	11	7	12.5	3.5	9.25	M2.5	1	1.2	2.4	25000	6.1×10 ⁻⁵	1100				71
	27	32.6	11	7	14.5	3.5	10.25		1.5	3	3	23000	8.2×10 ⁻⁵	1300				88
	34	37.4	12	9	16.5	4	13	M3	1.5	3.5	7	18000	2.5×10 ⁻⁵	1800				160
	39	47.2	15	11	20.5	5	14.5	M4	3.5	5	10	16000	5.1×10 ⁻⁵	3500				260
	44	47.2	15	11	23	5	17		7	14	14	14000	8.9×10 ⁻⁵	5500	0.3	2	±0.6	400
	56	61	20	14	28.5	6	21.25	M5	8	15	30	11000	2.9×10 ⁻⁴	10000				800

① 惯性力矩和重量按最大孔计算！



请按图示订货

型号	代码	D	d-e
DBM31	34	34	6 8 10
DBM41	34	34	6 8 10

DBM31—D34—d6—e10

② 可选加工

型号	代码	D	d-e	可选加工
DBM31	34	34	6 8 10	DC DD
DBM41	34	34	6 8 10	DC DD

DBM31—D34—d6—e10—DD



可选加工

可选加工	变更d/e孔径	d孔侧键槽加工	e孔侧键槽加工																		
代码	dh() eh()	DC	DD																		
技术说明	选型方法 dh3.1 eh4.5 ① 最小单位0.1 ② dh须≤eh ③ 选型时须将d(e)变更为dh(eh) <table><tr><th>D</th><th>dh·eh</th></tr><tr><td>15</td><td>3~5</td></tr><tr><td>19</td><td>4~8</td></tr><tr><td>25</td><td>5~12</td></tr><tr><td>27</td><td>6~14</td></tr><tr><td>34</td><td>6~16</td></tr><tr><td>39</td><td>8~20</td></tr><tr><td>44</td><td>8~22</td></tr><tr><td>56</td><td>18~28</td></tr></table> 	D	dh·eh	15	3~5	19	4~8	25	5~12	27	6~14	34	6~16	39	8~20	44	8~22	56	18~28	 选型方法 DC ① 不可与dh、eh 可选加工共用。	 选型方法 DD ① 不可与dh、eh 可选加工共用。
	D	dh·eh																			
	15	3~5																			
	19	4~8																			
	25	5~12																			
	27	6~14																			
	34	6~16																			
	39	8~20																			
	44	8~22																			
	56	18~28																			

① 当孔径≥6时才能选择键槽加工。

② 键槽加工尺寸见“产品简介”。



未税价(元)

数量	1~9	10~
价格	100%	另行报价



交货期

3