



加强筋

6.3/



型号		H		T		X	Y	A	B	P	P ₁	M	N		
代码	W			S45C	A6061/SUS304										
ZGB45 ZGB41 ZGB42 ZGB43 ZGB44 ZGB47	80	200	12	12		50	15	140	20			6	5		
		200A	16	16					8						
		250	12	12					6						
		250A	16	16			8								
		100	12	12			6								
		100A	16	16			8								
	100	150	12	12			6	25	25				4		
		150A	16	16			8								
		200	12	12			6								
		200A	16	16			8								
		250	12	12			6								
		250A	16	16			8								
	150	300	12	12		60	20	140	20					5	
		300A	16	16					8						
		250	12	12					6						
		250A	16	16					8						
300		12	12					6	35	40					
300A		16	16					8							
150	150	12	12		90	30	180	40					5		
	150A	16	16					8							
	200	12	12					6							
	200A	16	16					8							
	250	12	12					6	40	40					
	250A	16	16					8							
300	300	12	12				180	40					5		
	300A	16	16				8								

Technical drawing of a bolt head and profile. The top view shows a hexagonal head with dimensions: P (pitch), h (height), B (width across flats), H/2 (height from base to top of hex), and A (height from base to bottom of hex). The side view shows a profile with a 2-R3 fillet, W/2 (width of the base), C2 (fillet radius), X (distance from base to fillet start), Y (distance from fillet end to base), and W (total width). A detail view of the hex head shows T+0.1, N-M, and P+1 dimensions.



视角标准：第一视角

[illegible]

未税价(元)

数量	1~9	10~
价格	100%	另行报价