


精密型 快拧接头

- 直接头
- 弯接头
- 外螺纹

直接头

代码	类型	材质
J-XYV01	外螺纹 直接头	黄铜



视角标准：第一视角

型号	管外径D	公称型号	适用软管内径	R	A	B	L	E	C	S ₁	S ₂	有效断面积 (mm ²)	重量 (g)	
J-XYV01	4	1	2.5	R1/8	8	21.5	17.5	10.5	5.5	8	10	1	8.1	
		2		R1/4	11	25.5	19.5				14		14	
	6	1	4	R1/8	8	22	18	11	6	10	10	5.5	9.7	
		2		R1/4	11	26	20				14		16	
	8	1	6	R1/8	8	24		12	7	12	12	15	14	14
		2		R1/4	11	27	21				14		18	
		3		R3/8	12	29	22.7				17		27	
		4		R1/4	11	29.8	23.8				16		29	
	10	3	7.5	R3/8	12	31.8	25.5	14.8	9	16	17	21	36	
		4		R1/2	15	35.8	27.6				21		56	



型号	代码	D	公称型号	适用软管内径
J-XYV01	4	4	2	2.5

J-XYV01 - D4 - 1




● 优惠价
数量 1~29 30~
价格 100% 另行报价



弯接头

代码	类型	材质
J-XYV21	外螺纹 弯接头	黄铜



视角标准：第一视角

型号	管外径D	公称型号	适用软管内径	R	A	L ₁	L ₂	E ₁	E ₂	C	S ₁	S ₂	P ₁	P ₂	有效断面积 (mm ²)	重量 (g)
J-XYV21	4	1	2.5	R1/8	8	18	17	19.5	10.5	5.5	8	8	10	10	0.9	13
		2		R1/4	11	19	20	21.5					14			17
	6	1	4	R1/8	8	18.8	17	20	11	6	10	10	10	4	15	
		2		R1/4	11	19.8	20	22					19			
	8	1	6	R1/8	8	22.5	19.5	23	12	7	12	10	14	14	23	
		2		R1/4	11	22.5	19.5	23					25			
		3		R3/8	12	22.1	21.5	24.5					30			
		4		R1/4	11	27.2	24	28					47			
	10	3	7.5	R3/8	12	26.9	24	28	14.8	9	16	14	17	17	51	
		4		R1/2	15	28.6	27.5	29.5					21		66	



型号	代码	D	公称型号	适用软管内径
J-XYV21	4	4	2	2.5

J-XYV21 - D4 - 1



● 优惠价
数量 1~29 30~
价格 100% 另行报价



气调接头类
D8