


推力滚针轴承




代码	类型	材质
标准型		
BKL	单件	带保持器止推滚针
BNL		止推圈
BBL	套件	带保持器止推滚针+止推圈
		SUJ2+65Mn


单件
带保持器止推滚针
BKL



止推圈
BNL



组件
带保持器止推滚针+止推圈
BBL



止推圈在交货时可能会有少许变形，使用前请以同心圆的方式施加最低200N轴向负载即可使之平整。

视角标准：第一视角

型号		带保持器止推滚珠								止推圈×2		极限转速 (rpm)	基本额定负载(KN)		参考重量(g)		
代码	轴承型号	d	D	A	E	E ₁	d ₁	D ₁	B	Cr(动)	Cor(静)		BKL	BNL	BBL		
BKL BNL BBL	0414	4	14	-0.095 -0.365			13	5	4	14	-0.032 -0.302	15050	3.08	5.6	0.7	1	2.7
	0515	5	15				14	6	5	15	+0.200 +0.020	14420	3.325	6.44	0.8	1	2.8
	0619	6	19				18	7	6	19		13230	4.76	10.85	1	2	5
	0821	8	21				20	9	8	21	+0.245 +0.025	12460	5.46	13.58	2	2	6
	1024	10	24	-0.11 -0.44			23	12	10	24	-0.040 -0.370	11830	6.44	17.85			
	1226	12	26		2		25	14	12	26		10640	6.93	20.3	3		9
	1528	15	28				27	17	15	28	+0.302 +0.032	9240	7.91	25.2	4	3	10
	1730	17	30				29	19	17	30		8470	8.33	27.65	4	4	12
	2035	20	35	-0.12 -0.51			34	22	20	35		7350	9.17	32.55	5	5	15
	2542	25	42	+0.250 +0.004			41	29	25	42	+0.370 -0.040	5880	10.29	40.6	7	7	21
	3047	30	47	-0.13 -0.52			46	34	30	47		5110	11.41	49	8	8	24
	3552	35	52				51	39	35	52		4550	12.46	56.7	10	9	28
	4060	40	60	-0.14 -0.60			58	45	40	60		3920	19.6	79.8	16	12	40
	4565	45	65	+0.30 +0.05			63	50	45	65	+0.44 +0.05	3570	21	89.6	18	13	44
	5070	50	70	-0.15 -0.61	3	0 -0.01	68	55	50	70		3290	22.4	100.1	20	14	48
	5578	55	78				76	60	55	78	1 ±0.05	2980	26.6	130.2	28	18	64
	6085	60	85				83	65	60	85		2730	31.15	163.8	33	22	77
	6590	65	90	-0.17 -0.71			88	70	65	90	+0.52 +0.06	2560	39.76		35	24	83
	7095	70	95				93	74	70	95		2420	37.8	178.5	60	25	110
	75100	75	100				98	79	75	100	-0.072 -0.612	2280	38.5	185.5	61	27	115
80105	80	105				103	84	80	105		2170	39.2	196	63	28	119	
85110	85	110	-0.18 -0.72			108	89	85	110		2070	40.6	203	67	29	125	
90120	90	120		4		118	94	90	120		1890	51.1	283.5	86	39	164	
100135	100	135	+0.422 +0.072			133	105	100	135	+0.612 +0.072	1690	63.7	392	104	50	204	
110145	110	145	-0.21 -0.84			143	115	110	145		1560	67.9	434	122	55	232	
120155	120	155				153	125	120	155	-0.085 -0.715	1450	71.4	476	131	59	249	
130170	130	170	-0.23 -0.86			167	136	130	170		1330	93.1	588	205	65	335	
140180	140	180				177	146	140	180	+0.715 +0.085	1250	96.6	630	219	79	377	
150190	150	190	+0.485 +0.085		5	187	156	150	190	-0.10 -0.82	1180	100.1	672	232	84	400	
160200	160	200	-0.24 -0.96			197	166	160	200		1110	103.6	714	246	89	424	

d4~d8规格为尼龙保持架，d8以上规格为钢制保持架。

1Kg=9.81N



请按图示订货

代码	轴承型号	d
BKL	0414	4
BNL	0515	5

BKL0414



未税价(元)

● 优惠价

数量	1~9	10~
价格	100%	另行报价



交货期

5