



锁紧螺母

锁紧螺母/防松动垫圈 圆形



代码	类型	销售方式	锁紧螺母		防松动垫圈	
			材质	表面处理	材质	表面处理
BKJ51	圆型	单件	SS400	发黑	—	—
BKJ61			SUS304	—	—	—
BKJ56	防松动垫圈	—	—	—	SPCC	铬酸盐处理
BKJ57			—	—	SUS304	—
BKJ52	锁紧螺母+防松动垫圈	套件	SS400	发黑	SPCC	铬酸盐处理
BKJ62			SUS304	—	SUS304	—



锁紧螺母



防松动垫圈



型号		螺距	锁紧螺母					防松动垫圈							防松动垫圈齿数		
代码	公称尺寸		D	d	H	g	t	d ₁	K	E	F	T	V	D ₁	D ₂	BKJ52/56	BKJ57/62
锁紧螺母 BKJ51 BKJ61	M10	0.75	18	13	4	3		10	8.5	3	3		2	21	13	9	9
	M12		22	17				12	10.5					25	17		
	M15	1.0	25	21	5			15	13.5			1		28	21	11	11
	M17		28	24		4	2	17	15.5	4	4			32	24		
	M20		32	26	6			20	18.5					36	26		
	M25	1.5	38	32	7			25	23		5			42	32	13	13
	M30		45	38		5		30	27.5	5		2.5		49	38		
	M35		52	44	8			35	32.5					57	44	15	
	M40		58	50	9			40	37.5		6	1.2		62	50		
	M45		65	56	10	6	2.5	45	42.5	6	6			69	56	17	
	M50	70	61				50	47.5					74	61	17		
	M55	75	67	11			55	52.5					81	67		17	
	M60	80	73		7	3	60	57.5	7				86	73			
	M65	85	79				65	62.5		8	1.5		92	79			
	M70	92	85	12			70	66.5					98	85			
	M75	98	90	13	8	3.5	75	71.5	8			4	104	90			
	M80	105	95	15			80	76.5					112	95			
	M85	110	102				85	81.5			10		119	102			
	M90	120	108	16			90	86.5					126	108			
	M95	125	113	17	10	4	95	91.5	10		1.8		133	113		17	
M100	130	120	18			100	96.5					142	120				
M105*	140	126				105	100.5					145	126				
M110	145	133	19			110	105.5		12			154	133				
M115*	150	137				115	110.5				6	159	137		19		
M120	155	138	20	12	5	120	115	12				164	138				
M125*	160	148	21			125	120			14	2	170	148				
M130*	165	149				130	125					175	149				
M140*	180	160	22	14	6	140	135	14	16			192	160				
M150*	195	171	24			150	145					205	171				
M160*	210	182	25	16	7	160	154	16	18		2.5	217	182				
M170*	220	193	26			170	164					232	193				
M180*	230	203	27			180	174					242	203		19		
M190*	240	214	28	18	8	190	184	18	20			252	214				
M200*	250	226	29			200	194					262	226				

① 锁紧螺母与对应防松动垫圈规格相匹配。

① 带“*”尺寸不适用BKJ57/BKJ61/BKJ62。



请按图示订货

型号		螺距
代码	公称尺寸	
BKJ52	M10	0.75
BKJ61	M12	1.0

BKJ51—M10—0.75



未税价(元)

数量	优惠价	
	1~4	5~
价格	100%	另行报价



交货期
3




交货期
5

① BKJ51/52/56

① BKJ61/62/57

轴加工尺寸图



加工尺寸a最小值可参考F+1值进行加工
加工尺寸b最小值可参考d1+K+0.5值进行加工



Example
使用示例

① 用于锁紧机床主轴与零件间的配合，通过垫圈进行物理锁紧可保证一定的安装精度，主要应用在机电设备。

