

外螺纹·外圈滑动表面带保护层



正常系列(POS...)(SA...T/K)(NOS...)

杆端关节轴承



代码	类型	注油式	杆端		衬垫	内圈	
			材质	表面处理	材质	材质	热处理
BNC50	外螺纹	自润滑	碳钢	镀环保白锌	铜	轴承钢	淬火
BNC51							
BNC57							
BNC52							
BNC53			SUS304	—	PTFE	SUS304 SUS440	



注油式
BNC50



自润滑
BNC51
BNC52
BNC53
BNC57



注油式(POS...)

代码	型号	轴承规格	螺纹 旋向	d	B	d _K	C ₁	d ₂	G(6H)	h	L ₁ (min)	L ₂	R ₁	a°≈	静态径向 载荷容量(KN)	重量 (kg)
BNC50	POS5			5	8	7.7	6	16	M5×0.8	33	20	41	0.3	13	3.43	0.0125
	POS6			6	9	9	6.75	18	M6×1.0	36	22	45		14	4.9	0.019
	POS8			8	12	10.4	9	22	M8×1.25	42	25	53		16	6.86	0.032
	POS10			10	14	12.9	10.5	26	M10×1.5	48	29	61		17	10.8	0.054
	POS12			12	16	15.4	12	30	M12×1.75	54	33	69		18	16.7	0.085
	POS12-1			12	16	15.4	12	30	M12×1.25	54	33	69		18	16.7	0.085
	POS14		R (右旋)	14	19	16.9	13.5	34	M14×2.0	60	36	77		19	20.6	0.126
	POS16		L (左旋)	16	21	19.4	15	38	M16×2.0	66	40	85		20	25	0.185
	POS16-1			16	21	19.4	15	38	M16×1.5	66	40	85		20	25	0.185
	POS18			18	23	21.9	16.5	42	M18×1.5	72	44	93	0.6	21	29.4	0.26
	POS20			20	25	24.4	18	46	M20×1.5	78	47	101		22	34.3	0.34
	POS22			22	28	25.8	20	50	M22×1.5	84	51	109		23	41.2	0.435
	POS25			25	31	29.6	22	60	M24×2.0	94	57	124		24	72.5	0.65
	POS28			28	35	32.3	24	66	M27×2.0	103	62	136		25	75.5	0.96
	POS30			30	37	34.8	25	70	M30×2.0	110	66	145		26	92.2	1.07

自润滑(SA...T/K)

代码	型号	轴承规格	螺纹 旋向	d	B	C ₁	d ₂	G(6H)	h	L ₁ (min)	L ₂	R ₁ (min)	a°≈	额定负荷(KN) 动负荷 静负荷	重量 (kg)
BNC51 BNC52 BNC53	SA5T/K			5	8	6	18	M5×0.8	33	19	43.5	0.3	13	4.4 4.6	0.013
	SA6T/K*			6	9	6.75	20	M6×1.0	36	21	46.5		14	4.5 4.8	0.015
	SA8T/K*			8	12	9	24	M8×1.25	42	25	54.5		15	5.8 6.5	0.034
	SA10T/K*			10	14	10.5	28	M10×1.5	48	28	63.5		16	9.7 12	0.071
	SA12T/K*			12	16	12	32	M12×1.75	54	32	71.5		17	10.6 15	0.11
	SA14T/K*			14	19	13.5	36.5	M14×2.0	60	36	79		18	17 22	0.13
	SA16T/K*		R (右旋)	16	21	15	40	M16×2.0	66	37	87		19	19.7 27	0.22
	SA16T/K-1			16	21	15	40	M16×1.5	66	37	87		19	19.7 27	0.22
	SA18T/K		L (左旋)	18	23	16.5	45	M18×1.5	72	41	95	0.6	20	31.3 35	0.29
	SA20T/K			20	25	18	50	M20×1.5	78	45	104		21	29.8 40	0.36
	SA22T/K			22	28	20	54	M22×1.5	84	48	111		22	40.2 48	0.49
	SA25T/K			25	31	22	60	M24×2.0	94	55	125		23	44 55	0.65
	SA28T/K			28	35	24	66	M27×2.0	103	62	136		24	52.2 65	0.87
	SA30T/K			30	37	25	71	M30×2.0	110	66	146.5		25	60.2 78	1.1
BNC51	SA35T/K			35	43	28	81	M36×2.0	140	85	180.5		26	—	1.64
	SA40T/K			40	49	33	91	M42×2.0	150	90	195.5	1.0	27	—	2.4
	SA40T/K			40	49	33	91	M42×2.0	150	90	195.5		27	—	2.4
	SA50T/K			50	60	45	117	M48×2.0	185	105	243.5		28	—	4.8

① BNC53仅适用带*号规格。

自润滑(NOS...)

代码	型号	轴承规格	螺纹 旋向	d	B	C ₁	d ₂	G(6H)	h	L ₁ (min)	L ₂	R ₁	a°≈	静态径向 载荷容量(KN)	重量 (kg)
BNC57	NOS3			3	6	4.5	12	M3×0.5	27	15	33	0.3	10	1.57	0.0045
	NOS4			4	7	5.3	14	M4×0.7	30	17	37		11	2.25	0.007
	NOS5			5	8	6	16	M5×0.8	33	20	42.5		12	3.43	0.0125
	NOS6			6	9	6.75	18	M6×1.0	36	22	46.5		13	4.9	0.019
	NOS8			8	12	9	25	M8×1.25	42	25	54.5		14	6.86	0.032
	NOS10		R (右旋)	10	14	10.5	29	M10×1.5	48	29	62.5		15	9.41	0.054
	NOS12		L (左旋)	12	16	12	33	M12×1.75	54	33	70.5		16	11	0.085
	NOS14			14	19	13.5	37	M14×2.0	60	36	78.5		17	15.2	0.126
	NOS16			16	21	15	43	M16×2.0	66	40	87.5	0.6	18	20.2	0.185
	NOS18			18	23	16.5	47	M18×1.5	72	44	95.5		19	25.2	0.26
	NOS20			20	25	18	51	M20×1.5	78	47	103.5		20	27.8	0.34
	NOS22			22	28	20	54	M22×1.5	84	51	111.5		21	35.9	0.435



代码	型号	轴承规格	螺纹旋向	d
BNC51	SA5T/K	R(右旋)		5
BNC51	SA6T/K	L(左旋)		6

BNC51 — SA5T/K — R



优惠价
数量 1~9 10~
价格 100% 另行报价

