

# 加宽型 · 标准型/外螺纹型

## 标准型

# 圆皮带用惰轮




轴承精度：GB/T 307.1 0 级  
相当于：JIS B 1514 0 级



来图定制


标准型

ENY01/02/11/21



外螺纹型

ENY51/52/61/71



- ① 轴承为粘接式。
- ② 外螺纹部销为粘接。
- ③ 3D模型仅供参考，具体尺寸请以参数表为准，注意选型。

视角标准：第一视角

| 型号                                       | 代码   | A   | R | d  | P  | dh | D   | D <sub>1</sub> | T  | t    | B | 使用轴承      | M   | G | F  | F <sub>1</sub> | 适用圆皮带直径 |
|------------------------------------------|------|-----|---|----|----|----|-----|----------------|----|------|---|-----------|-----|---|----|----------------|---------|
| 标准型<br>ENY01<br>ENY02<br>ENY11<br>ENY21  | (15) |     |   | 3  | 10 | 8  | 17  | 13             | 10 | 6.5  | 4 | BAF623ZZ  |     |   |    |                | 2       |
|                                          | (20) | 1   |   | 5  | 16 | 13 | 32  | 28             | 12 | 9    | 5 | BAF625ZZ  |     |   |    |                |         |
|                                          | (30) |     |   | 4  | 13 | 11 | 22  | 17             | 10 | 7.5  |   | BAF624ZZ  |     |   |    |                | 3       |
|                                          | (20) | 1.5 |   | 6  | 19 | 16 | 32  | 27             | 12 | 9    | 6 | BAF626ZZ  | M6  | 3 | 10 | 1              |         |
|                                          | (23) |     |   | 5  | 16 | 13 | 25  | 19             | 10 | 7.5  | 5 | BAF625ZZ  |     |   |    |                |         |
|                                          | 28   |     |   | 6  | 19 | 16 | 30  | 24             | 12 | 9    | 6 | BAF626ZZ  | M6  | 3 | 10 | 1              |         |
|                                          | 30   |     |   |    |    |    | 32  | 26             |    |      |   |           |     |   |    |                | 4       |
|                                          | 40   | 2   |   | 10 | 26 | 23 | 42  | 36             |    |      |   | BAY6000ZZ | M8  | 5 | 12 |                |         |
|                                          | 48   |     |   | 12 | 28 | 25 | 50  | 44             | 15 | 11.5 | 8 | BAY6001ZZ | M10 | 6 | 15 | 1.5            |         |
|                                          | 60   |     |   |    |    |    | 62  | 56             |    |      |   |           |     |   |    |                |         |
|                                          | (23) |     |   | 5  | 16 | 13 | 25  | 18             | 10 | 7.5  | 5 | BAF625ZZ  |     |   |    |                |         |
|                                          | 28   |     |   | 6  | 19 | 16 | 30  | 23             | 12 | 9    | 6 | BAF626ZZ  | M6  | 3 | 10 | 1              |         |
|                                          | 40   | 2.5 |   | 10 | 26 | 23 | 42  | 35             |    |      |   | BAY6000ZZ | M8  | 5 | 12 |                | 5       |
|                                          | 48   |     |   |    |    |    | 50  | 43             | 15 | 11.5 | 8 |           |     |   |    | 1.5            |         |
|                                          | 50   |     |   | 12 | 28 | 25 | 52  | 45             |    |      |   | BAY6001ZZ | M10 | 6 | 15 |                |         |
|                                          | 60   |     |   |    |    |    | 62  | 55             |    |      |   |           |     |   |    |                |         |
| 外螺纹型<br>ENY51<br>ENY52<br>ENY61<br>ENY71 | 28   |     |   | 6  | 19 | 16 | 30  | 22             | 12 | 9    | 6 | BAF626ZZ  | M6  | 3 | 10 | 1              |         |
|                                          | 38   |     |   | 10 | 26 | 23 | 40  | 32             |    |      |   | BAY6000ZZ | M8  | 5 | 12 |                |         |
|                                          | 48   |     |   |    |    |    | 50  | 42             |    |      |   |           |     |   |    |                |         |
|                                          | 50   | 3   |   |    |    |    | 52  | 44             |    |      |   |           |     |   |    |                | 6       |
|                                          | 60   |     |   |    |    |    | 62  | 54             |    |      |   |           |     |   | 15 | 1.5            |         |
|                                          | 80   |     |   | 12 | 28 | 25 | 82  | 74             | 15 | 11.5 | 8 | BAY6001ZZ |     |   |    |                |         |
|                                          | 100  |     |   |    |    |    | 102 | 94             |    |      |   |           |     |   |    |                |         |
|                                          | 50   |     |   |    |    |    | 52  | 42             |    |      |   |           |     |   |    |                |         |
|                                          | 60   |     |   |    |    |    | 62  | 52             |    |      |   |           |     |   |    | 1.5            |         |
|                                          | 80   | 4   |   |    |    |    | 82  | 72             |    |      |   |           | M10 | 6 | 15 |                | 8       |
|                                          | 100  |     |   | 15 | 32 | 28 | 102 | 92             | 16 | 12.5 | 9 | BAY6002ZZ |     |   |    | 1              |         |
|                                          | 120  |     |   |    |    |    | 122 | 112            |    |      |   |           |     |   |    |                |         |
|                                          | 60   |     |   | 12 | 28 | 25 | 62  | 50             | 15 | 11.5 | 8 | BAY6001ZZ |     |   |    | 1.5            |         |
|                                          | 80   |     |   |    |    |    | 82  | 70             |    |      |   |           |     |   |    |                |         |
|                                          | 100  | 5   |   |    |    |    | 102 | 90             |    |      |   |           |     |   | 15 |                | 10      |
|                                          | 120  |     |   | 15 | 32 | 28 | 122 | 110            | 16 | 12.5 | 9 | BAY6002ZZ |     |   |    | 1              |         |
|                                          | 140  |     |   |    |    |    | 142 | 130            |    |      |   |           |     |   |    |                |         |

① 带( )的尺寸不适用于外螺纹型。

③ 可选加工



请按图示订货

| 型号           | 代码 | A | R |
|--------------|----|---|---|
| ENY01        | 20 |   | ① |
| ENY02        | 30 |   | ① |
| ENY01—A20—R1 |    |   |   |

| 型号              | 代码 | A | R | 可选加工代码 |
|-----------------|----|---|---|--------|
| ENY01           | 20 |   | ① | DC     |
| ENY02           | 30 |   | ① | DC     |
| ENY01—A20—R1—DC |    |   |   |        |



未税价(元)

| 优惠价 | 数量   | 1~9  | 10~ |
|-----|------|------|-----|
| 价格  | 100% | 另行报价 |     |




ENY02/52



① 其余



可选加工

| 代码  | 技术说明                                                                              |                                                                                                                                                                                            |        |    |   |       |     |       |   |       |     |       |
|-----|-----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|----|---|-------|-----|-------|---|-------|-----|-------|
| DC  | 切割D <sub>1</sub> 尺寸                                                               | <div>选型方法 DC</div> <div>① 切割D<sub>1</sub>尺寸，减小外径；<br/>② 外径切割的加工面可能不进行表面处理；<br/>③ 适用皮带半径3.0以下规格；<br/>④ 仅适用标准型产品。</div>                                                                      |        |    |   |       |     |       |   |       |     |       |
|     |  | <table><tr><th>适用皮带半径</th><th>DC</th></tr><tr><td>1</td><td>A+0.8</td></tr><tr><td>1.5</td><td>A+1.2</td></tr><tr><td>2</td><td>A+1.6</td></tr><tr><td>2.5</td><td>A+1.8</td></tr></table> | 适用皮带半径 | DC | 1 | A+0.8 | 1.5 | A+1.2 | 2 | A+1.6 | 2.5 | A+1.8 |
|     | 适用皮带半径                                                                            | DC                                                                                                                                                                                         |        |    |   |       |     |       |   |       |     |       |
| 1   | A+0.8                                                                             |                                                                                                                                                                                            |        |    |   |       |     |       |   |       |     |       |
| 1.5 | A+1.2                                                                             |                                                                                                                                                                                            |        |    |   |       |     |       |   |       |     |       |
| 2   | A+1.6                                                                             |                                                                                                                                                                                            |        |    |   |       |     |       |   |       |     |       |
| 2.5 | A+1.8                                                                             |                                                                                                                                                                                            |        |    |   |       |     |       |   |       |     |       |