


① 一字槽紧定螺钉

代码	类型	螺纹	材质		表面处理
			国标	相当	
TAY52	平端	粗牙	0Cr18Ni9	SUS304	—



视角标准：第一视角

① 适用标准：GB/T 73-1985

型号	代码	M	L				n		h		d		
			2	3	4	6	8	Max	Min	Max	Min	Max	Min
TAY52	2	2	3	4	6	8	0.45	0.31	0.84	0.64	1	0.75	
	2.5	3	4	5			0.6	0.46	0.95	0.72	1.5	1.25	
	3				5	6	8	10	14		2	1.75	
	4	4	6	16			0.8	0.66	1.42	1.12	2.5	2.25	
	5	4	6	8	10		1	0.86	1.63	1.28	3.5	3.2	
	6		6	8		20	30	1.2	1.06	2	1.6	4	3.7
	8		6				25	1.51	1.26	2.5	2	5.5	5.2



请按图示订货

型号	L
代码 M	
(TAY52)	(3) (5) 6 8
	4 4 6
TAY52—M3—L5	



未税价(元)

● 优惠价

数量	1~99	100~
价格	100%	另行报价




交货期

7

② 内六角喉塞

代码	类型	材质	表面处理
TAY36	内六角喉塞	ML40Cr	发黑

① 规格M≥27，材质为SCM440。



视角标准：第一视角


① 适用标准：DIN 906



Example 使用示例

① 压缩弹簧的压板

TAY36/TAN系列(P71)




② 保护未使用的螺孔

TAY36/TAN系列(P71)



③ 齿轮箱等注油孔的盖子

TAY36/TAN系列(P71)




型号	代码	M	P 螺距	h		S	L
				Min	Max		
TAY36	10					5	
	12					6	10
	14		1.5	6	6.5	8	
	16					10	
	18					12	
	20			6.5	7		
	22			6	6.5		

型号	代码	M	P 螺距	h		S	L
				Min	Max		
TAY36	24		1.5	6	6.5	14	12
	26						
	27						
	28						
	30						
	33					17	

③ 内六角圆柱头喉塞

代码	类型	材质	表面处理	适用标准
TAY40	内六角圆柱头喉塞	SUS304	—	DIN 908




视角标准：第一视角



④ 六角头喉塞

代码	类型	材质	表面处理	适用标准
TAY41	六角头喉塞	SUS304	—	DIN 910



视角标准：第一视角



型号	代码	M	P 螺距	D	K Min	h Min	S	L
	12			17		7	6.15	
	14			19	3			12
	16			21			8.19	
	18			23				14
	20	1.5		25		7.5	10.19	
	22			27				14
	24			29	4			
	26			31			12.23	
	27			32		9		16
	30			36			17.23	

型号	代码	M	P 螺距	D	K Max	h Max	S	L
	12			17				
	14			19	3.5	6.5		11
	16			21				
	18			23				17
	20	1.5		25		8.5		13
	22			27				
	24			29	4.5	9.5		22
	26			31				
	27			32		10.5		24
	30			36				15

⑤ 内六角圆柱头喉塞



请按图示订货

型号	L
代码 M	
(TAY40)	(10) (12)
TAY40—M10	



未税价(元)

● 优惠价

数量	1~49	50~
价格	100%	另行报价



交货期

5