

代码	类型	材质	内径公差	外径公差
E-OCR03	标准型 方法兰型	高强度黄铜合金镶嵌固体润滑剂	F7	h7




特点

- 自润滑、免维护，适用于中轻载、低速运动；
- 适用于直线、旋转运动。

① 与本产品相配轴径公差：d8重载、e7轻载、g6高精度(仅供参考)。

② 与本产品相配固定座直径公差：H7(仅供参考)。

③ 产品压入座孔时在座孔端部或者内壁涂抹少许润滑油，利用油压机或台钳将其慢慢压入座孔，请勿用力敲击产品，以免引起产品变形。



视角标准：第一视角

型号	L	D _{h7}	H	T	h	d ₁	d ₂	P.C.D	W	适用内六角薄圆柱头螺钉 (需另行购买)
代码	d _{F7}									
6	15 20 25	10	25					17	20	
8	15 20 25 30	12	27	4	2.3	3.3	6	19	22	M3×10(4个)
10	20 25 30	14	29					21	23	
12	20 25 30 35	18	36					26	28	
13	20 25 30 35 40	19	37	5	3	4.3	7.5	27	29	M4×12(4个)
16	20 25 30 35 40 50	22	40					30	31	
20	20 25 30 35 40 50 60	28	49					38	38	
25	25 30 35 40 50 60 70	33	54	6	3.7	5.3	9	43	42	M5×16(4个)
30	30 35 40 50 60 70	38	63					50	50	
35	40 50 60 70 80	44	69	8	4.3	6.3	11	56	54	M6×20(4个)
40	40 60 70 80 100	50	82	10	5.3	8.5	14	66	64	M8×25(4个)
50	70 80 100	62	94					78	73	



请按图示订货

型号	L
代码	d
E-OCR03	6 8 15 20 25
	8 15 20 25

E-OCR03 — d6 — L15



未税价(元)

优惠价

数量	1~9	10~
价格	100%	另行报价



交货期

18