

代码	类型		材质		
			国标	相当	
BPT01	进口型	无内圈型	圆柱型	GCr15	SUJ2
BPT02				9Cr18Mo	SUS440C
BPT21			球面型	GCr15	SUJ2
BPT22				9Cr18Mo	SUS440C


◎ 圆柱型D公差：

D	公差
16	$0_{-0.008}^0$
19~30	$0_{-0.009}^0$
32~47	$0_{-0.011}^0$
52~80	$0_{-0.013}^0$
85~90	$0_{-0.015}^0$


◎ 球面型D公差：.0.05



圆柱型
BPT01/02



球面型
BPT21/22



❶ 不承诺品牌。



型号		密封圈	drf6		D	B	r	基本额定负荷		轨迹表面负荷容量		极限转速	重量
代码	规格							C(KN)	Co(KN)	圆柱型外圈	球面型外圈		
圆柱型 BPT01 BPT02	5		7	$+0.022_{+0.013}$	16	7.8	0.5	2.74	2.39	2.35	1.08	30000	8.9
	6		10		19			4.12	4.55	3.53	1.37	20000	13.9
	8		12		24	9.8	1	5.68	5.89	4.02	1.86	17000	23.5
	10		14	$+0.027_{+0.016}$	30			9.7	9.67	5.59	2.45	15000	42.5
	12		16		32	11.8		10.4	10.9	5.98	2.74	13000	49.5
	15		20		35			12.3	14.3	6.57	3.14	10000	50
球面型 BPT21 BPT22	17	—	22		40		1.5	17.4	20.9	10.9	3.72	9500	90
	20	(无密封圈)	25	$+0.033_{+0.020}$	47	15.8		19.2	24.5	12.7	4.61	8500	135
	25		30		52			20.7	28.4	14.1	5.29	7000	152
	30		38		62			30.3	45.4	22.1	6.66	5500	255
	35		42	$+0.041_{+0.025}$	72			32.2	50.6	25.7	8.13	5000	375
	40		50		80	19.8		35.7	61.6	26.9	9.31	4000	420
	45		55	$+0.049_{+0.030}$	85		2	37.1	66.4	28.5	10.1	4000	460
	50		60		90			38.7	71.8	30.2	11.0	3500	500

❶ 上表中极限转速数值适用于润滑脂润滑的型号。采用油润滑的型号容许使用上限为上述数值的130%。



型号		密封圈	dr
代码	规格		
BPT01	5	—	7
BPT02	6	(无密封圈)	10

BPT01—5



● 优惠价
数量 | 1~9 | 10~
价格 | 100% | 另行报价

