



锁紧螺母

锁紧螺母/防松动垫圈 圆型




代码	类型	销售方式	锁紧螺母		防松动垫圈	
			材质	表面处理	材质	表面处理
BKJ51	圆型	单件	SS400	发黑	—	—
BKJ61			SUS304	—	—	—
BKJ56		套件	—	—	SPCC	铬酸盐处理
BKJ57			—	—	SUS304	—
BKJ52	锁紧螺母+防松动垫圈	套件	SS400	发黑	SPCC	铬酸盐处理
BKJ62			SUS304	—	SUS304	—



锁紧螺母



防松动垫圈



视角标准：第一视角

型号		螺距	锁紧螺母						防松动垫圈								
代码	公称尺寸		D	d	H	g	t	d ₁	K	E	F	T	V	D ₁	D ₂	齿数	
锁紧螺母 BKJ51 BKJ61	M10	0.75	18	13	4	3		10	8.5	3	3		2	21	13	9	
	M12		22	17				12	10.5					25	17		
	M15	1.0	25	21	5			15	13.5			1		28	21		
	M17		28	24		4	2	17	15.5	4	4			32	24		
	M20		32	26	6			20	18.5					36	26	13	
	M25		38	32	7			25	23		5		2.5	42	32		
	M30	1.5	45	38		5		30	27.5	5				49	38		
	M35		52	44	8			35	32.5					57	44		
	M40		58	50	9			40	37.5		6	1.2		62	50	15	
	M45		65	56	10	6	2.5	45	42.5	6				69	56		
	M50		70	61				50	47.5					74	61	17	
	M55		75	67	11			55	52.5					81	67		
	M60		80	73		7	3	60	57.5	7				86	73		
	M65		85	79	12			65	62.5		8	1.5		92	79		
	M70		92	85				70	66.5					98	85		
	M75		98	90	13	8	3.5	75	71.5	8			4	104	90		
	M80		105	95	15			80	76.5					112	95		
	M85		110	102				85	81.5		10			119	102		
	M90		120	108	16			90	86.5			10		126	108		
	M95	2.0	125	113	17	10	4	95	91.5	10		1.8		133	113		
M100	130		120				100	96.5					142	120			
M105*	140		126	18			105	100.5		12			145	126			
M110	145		133				110	105.5					154	133			
M115*		150	137	19			115	110.5				6	159	137	19		
M120		155	138	20	12	5	120	115	12				164	138			
M125*		160	148				125	120		14			170	148			
M130*		165	149	21			130	125			2		175	149			
M140*		180	160	22		14	140	135	14	16			192	160			
M150*		195	171	24		6	150	145					205	171			
M160*		210	182	25			160	154					217	182			
M170*		220	193	26	16	7	170	164	16	18		8	232	193			
M180*	3.0	230	203	27			180	174			2.5		242	203			
M190*		240	214	28	18	8	190	184	18	20			252	214			
M200*		250	226	29			200	194					262	226			

① 锁紧螺母与对应防松动垫圈规格相匹配。

② 带“*”尺寸不适用BKJ57/BKJ61/BKJ62。

③ 轴加工尺寸图



请按图示订货


代码	公称尺寸	螺距
BKJ51	M10	0.75
BKJ61	M12	1.0



④ BKJ51/52/56



④ BKJ61/62/57




加工a尺寸可参考F值进行加工
加工b尺寸可参考d1-K值进行加工

EX

Example
使用示例

⑤ 用于锁紧机床主轴与零件间的配合，通过垫圈进行物理锁紧可保证一定的安装精度，主要应用在机电设备。



未税价(元)

优惠价

数量	1~4	5~
价格	100%	另行报价