

塑料滑动轴承

高耐介质型 直柱型/肩型

无油衬套


E1

代码	类型	材质	使用温度
OBE03	高耐介质型	工程塑料	-40°C~+200°C
OBE04			


- 特点: 自润滑, 免维护, 耐高温, 适合潮湿环境中使用。
- 用途: 广泛适用在潮湿和水下环境。



直柱型
OBE03



肩型
OBE04



推荐配套轴公差: h9

视角标准: 第一视角

直柱型

型号	d	d公差	L	D	a	b
OBE03	3	+0.046 +0.006	3 5	4.5		
	4		4 6	5.5		0.3
	5	+0.058 +0.010	5	7		
	6		4 6 10	8		
	8		5 8 10 15	10		
	10	+0.071 +0.013	6 10 12 15	12		0.5
	12		10 12 15 20	14		
	14		20	16		
	15	+0.086 +0.016	15	17		
	16		15 20 25	18	0.5	
	18		15 20 25	20		0.8
	20		20 30	23		
	25	+0.104 +0.020	15 20	28		
	30		20 25 30 40	34		
	35		20 40	39		
40		20 30 50	44			
45	+0.125 +0.025	50	50		1.2	
50		40	55			

肩型

型号	d	d公差	L	D	H	T	b
OBE04	3	+0.046 +0.006	5	4.5	7.5	0.75	
	4		3 4 6	5.5	9.5		0.3
	5	+0.058 +0.010	5	7	11		
	6		4 6 10	8	12		
	8		5.5 7.5 10 15	10	15		
	10	+0.071 +0.013	5 9 10 12 15 17	12	18		0.5
	12		7 10 12 15 20	14	20	1	
	14		12	16	22		
	15	+0.086 +0.016	17	17	23		
	16		17	18	24		
	18		12 17	20	26		0.8
	20		11.5 16.5 21.5 30	23	30	1.5	
	25	+0.104 +0.020	30	28	35		
	30		40	34	42		
	35		26	39	47		
40		40	44	52	2		
45	+0.125 +0.025	50	50	58		1.2	
50		50	55	63			

直柱型

型号	d	d公差	L
OBE04	3	+0.046 +0.006	5
	4	+0.058 +0.010	3 4 6

OBE04—d3—L5



未税价(元)

优惠价

数量	1~9	10~
价格	100%	另行报价



交货期

7



请按图示订货