


长度选择

代码	类型		材质	颜色
UCP01	沉孔型	长度选择	聚甲醛	白色
UCP06			MC尼龙标准级	蓝色

使用环境温度

聚甲醛	-45~95°C
MC尼龙标准级	-40~120°C




代码	型号	D	T 选择	H	V	P
聚甲醛 UCP01	10	6 8		3.5	6	3.3
	12	6 8 10		4.5	8	4.3
	14	6 8 10 12		5.5	10	5.3
	15	8 10 12 15		6.5	11	6.3
MC尼龙 标准级 UCP06	20	10 12 15		8.5	14	8.5
	30	12 15 20		10.5	18	10.5
	40	12 15 20 25				
	50	15 20 25				
	60	15 20 25				

尺寸指定

代码	类型		材质	颜色
UCP51	沉孔型	尺寸指定	聚甲醛	白色
UCP52			黑色	
UCP56			MC尼龙标准级	蓝色
UCP57			象牙色	
UCP66			PEEK	灰色

使用环境温度

聚甲醛	-45~95°C
MC尼龙标准级	-40~120°C
PEEK	-50~250°C



型号	D	V	P	H	T
代码	最小单位0.5	最小单位0.1	最小单位0.1	最小单位0.1	最小单位0.1
聚甲醛 UCP51 UCP52	MC尼龙标准级 UCP56	10.0~20	5.0~55.0	3.0~53.0	1.0~48.0
	PEEK UCP66	20.5~30			
		30.5~40			
		40.5~50			
		50.5~60			



代码	变更内孔为螺孔	技术说明																														
MC( ) (粗牙) MD( ) (细牙)		<p>选型方法 MC4</p> <p>螺距表</p> <table border="1"> <thead> <tr> <th>螺纹直径 MC/MD</th> <th>MC (粗牙)</th> <th>MD (细牙)</th> </tr> </thead> <tbody> <tr><td>4</td><td>0.7</td><td>0.5</td></tr> <tr><td>5</td><td>0.8</td><td></td></tr> <tr><td>6</td><td>1.0</td><td>0.75</td></tr> <tr><td>8</td><td>1.25</td><td></td></tr> <tr><td>10</td><td>1.5</td><td>1.0</td></tr> <tr><td>12</td><td>1.75</td><td></td></tr> <tr><td>16</td><td>2.0</td><td></td></tr> <tr><td>18</td><td>—</td><td>1.5</td></tr> <tr><td>20</td><td>2.5</td><td></td></tr> </tbody> </table>	螺纹直径 MC/MD	MC (粗牙)	MD (细牙)	4	0.7	0.5	5	0.8		6	1.0	0.75	8	1.25		10	1.5	1.0	12	1.75		16	2.0		18	—	1.5	20	2.5	
螺纹直径 MC/MD	MC (粗牙)	MD (细牙)																														
4	0.7	0.5																														
5	0.8																															
6	1.0	0.75																														
8	1.25																															
10	1.5	1.0																														
12	1.75																															
16	2.0																															
18	—	1.5																														
20	2.5																															

长度选择

代码	D	T	H
UCP91	10	6 8	3.5
UCP06	12	6 8 10	4.5

尺寸指定

型号	D	V	P	H	T
代码	最小单位0.5	最小单位0.1	最小单位0.1	最小单位0.1	最小单位0.1
UCP51	10.0~20	5.0~55.0	3.0~53.0	1.0~48.0	1.0~50
UCP52					

UCP01—D10—T8

UCP51—D10—V7—P4—H7—T10

可选加工

型号	D	V	P	H	T	可选加工代码
代码	最小单位0.5	最小单位0.1	最小单位0.1	最小单位0.1	最小单位0.1	
UCP51	10.0~20	5.0~55.0	3.0~53.0	1.0~48.0	1.0~50	MC( ) MD( )
UCP52						

UCP51—D10—V7—P4—H7—T10—MC4



● 优惠价  
数量 1~99 100~  
价格 100% 另行报价

