


螺钉夹紧型
高刚性高速度 铝合金

膜片式联轴器




代码	类型	材质		表面处理	附件
		主体	膜片		
DBM52	螺钉夹紧型	单膜片	铝合金	本色阳极氧化	内六角圆柱头螺钉
DBM62		双膜片	不锈钢		



单膜片
DBM52



双膜片
DBM62



视角标准：第一视角

型号		d-e																							
代码	D																								
单膜片 DBM52	15	d	3			4		5		6															
		e	3 4 5 6			4 5 6		5 6		6															
	19	d	4			5		6		6.35		7		8											
		e	4 5 6 6.35 7 8			5 6 6.35 7 8		6 6.35 7 8		6.35 7 8		7 8		8											
	25	d	5			6		6.35		8		9.525		10		12									
		e	5 6 6.35 8 9.525 10 12			6 6.35 8 9.525 10 12		6.35 8 9.525 10 12		8 9.525 10 12		9.525 10 12		10 12		12									
	27	d	5			6		6.35		8		9.525		10		12		14							
		e	5 6 6.35 8 9.525 10 12 14			6 6.35 8 9.525 10 12 14		6.35 8 9.525 10 12 14		8 9.525 10 12 14		9.525 10 12 14		10 12 14		12 14		14							
	34	d	6			6.35		8		9.525		10		12		14		16							
		e	6 6.35 8 9.525 10 12 14 16			6.35 8 9.525 10 12 14 16		8 9.525 10 12 14 16		9.525 10 12 14 16		10 12 14 16		12 14 16		14 16		16							
39	d	8			9.525		10		12		14		15		16		18		20						
	e	8 9.525 10 12 14 15 16 18 20			9.525 10 12 14 15 16 18 20		10 12 14 15 16 18 20		12 14 15 16 18 20		14 15 16 18 20		15 16 18 20		16 18 20		18 20		20						
双膜片 DBM62	44	d	8			9.525		10		12		14		15		16		18		20		22			
		e	8 9.525 10 12 14 15 16 18 20 22			9.525 10 12 14 15 16 18 20 22		10 12 14 15 16 18 20 22		12 14 15 16 18 20 22		14 15 16 18 20 22		15 16 18 20 22		16 18 20 22		18 20 22		20 22		22			
56		d	10			12		14		15		16		18		20		22		24		25		28	
		e	10 12 14 15 16 18 20 22 24 25 28			12 14 15 16 18 20 22 24 25 28		14 15 16 18 20 22 24 25 28		15 16 18 20 22 24 25 28		16 18 20 22 24 25 28		18 20 22 24 25 28		20 22 24 25 28		22 24 25 28		24 25 28		25 28		28	
64		d	15			16		18		20		22		24		25		28		30		32		35	
		e	15 16 18 20 22 24 25 28 30 32 35			16 18 20 22 24 25 28 30 32 35		18 20 22 24 25 28 30 32 35		20 22 24 25 28 30 32 35		22 24 25 28 30 32 35		24 25 28 30 32 35		25 28 30 32 35		28 30 32 35		30 32 35		32 35		35	
79		d	20			22		24		25		28		30		32		35		38		40		42	
		e	20 22 24 25 28 30 32 35 38 40 42			22 24 25 28 30 32 35 38 40 42		24 25 28 30 32 35 38 40 42		25 28 30 32 35 38 40 42		28 30 32 35 38 40 42		30 32 35 38 40 42		32 35 38 40 42		35 38 40 42		38 40 42		40 42		42	
98		d	25			28		30		32		35		38		40		42		45		50			
		e	25 28 30 32 35 38 40 42 45 50			28 30 32 35 38 40 42 45 50		30 32 35 38 40 42 45 50		32 35 38 40 42 45 50		35 38 40 42 45 50		38 40 42 45 50		40 42 45 50		42 45 50		45 50		50			

膜片式联轴器

螺钉夹紧型


高刚性高速度 铝合金

型号		L	L ₁	F	L ₂	A	M	锁紧 扭矩 (N·m)	额定 扭矩 (N·m)	最大 扭矩 (N·m)	最高 转速 (r/min)	静态 扭转刚性 (N·m/rad)	惯性 力矩 (kg·m ²)	容许安装偏差			重量 (g)
代码	D													径向 (mm)	角向 (°)	轴向 (mm)	
单膜片 DBM52	15	16	7.7	2.5		5	M2	0.45	0.6	1.2	42000	0.11×10 ⁻³	2.6×10 ⁻⁷	0.01	0.7		6.6
	19	20.2	9.5	2.9		7			1.5	3	33000	0.32×10 ⁻³	6.3×10 ⁻⁷			±0.1	13
	25			3.5		9	M2.5	1	3	6	25000	1.2×10 ⁻³	2.3×10 ⁻⁶			±0.15	25
	27			3.8		10			3.3	6.6	23000	1.8×10 ⁻³	3.1×10 ⁻⁶			±0.2	27
	34	27.1	13.1	4		12	M3	1.5	6.3	12.6	18000	3.9×10 ⁻³	9.2×10 ⁻⁶			±0.25	52
	39					14			12	24	16000	6.0×10 ⁻³	2.0×10 ⁻⁵	0.02	1		84
	44	33.8	16.3	4.5		17	M4	3.5	15	30	14000	7.9×10 ⁻³	3.3×10 ⁻⁵			±0.3	107
	56	44.1	21.3	6		21	M5	8	37.5	75	11000	1.4×10 ⁻²	1.1×10 ⁻⁴			±0.35	233
	64	49.2	24	7		24	M6	14	50	100	9800	1.6×10 ⁻²	2.1×10 ⁻⁴			±0.45	328
	79	62.5	30			29	M8	28	100	200	7900	2.3×10 ⁻²	6.7×10 ⁻⁴			±0.55	748
	98	66.5	32			38			280	560	6400	5.2×10 ⁻²	1.7×10 ⁻³			±0.65	1120
	15	22.3	7.7	2.5	5.7	5	M2	0.45	0.6	1.2	42000	0.1×10 ⁻³	3.0×10 ⁻⁷	0.1	1.4		9.4
双膜片 DBM62	19	26.3	9.5	2.9	5.5	7	M2.5	1	1.5	3	33000	0.3×10 ⁻³	8.8×10 ⁻⁷	0.12		±0.2	17
	25			3.5		9			3	6	25000	1.0×10 ⁻³	3.4×10 ⁻⁶			±0.3	35
	27	32.2	11.6	3.8	7.8	10			3.3	6.6	23000	1.4×10 ⁻³	4.4×10 ⁻⁶	0.15		±0.4	39
	34	37.4	13.1	4	9.4	12	M3	1.5	6.3	12.6	18000	2.5×10 ⁻³	1.3×10 ⁻⁶	0.2		±0.5	75
	39					14			12	24	16000	4.7×10 ⁻³	2.9×10 ⁻⁵	0.25	2		123
	44	47.8	16.3	4.5	12.8	17	M4	3.5	15	30	14000	6.4×10 ⁻³	4.7×10 ⁻⁵			±0.6	156
	56	62	21.3	6	16.4	21	M5	8	37.5	75	11000	1.2×10 ⁻²	1.7×10 ⁻⁴	0.3		±0.7	340
	64	75	24	7	24.6	24	M6	14	50	100	9800	1.5×10 ⁻²	3.3×10 ⁻⁴	0.35		±0.9	490
	79	98.8	30	9	33.8	29	M8	28	100	200	7900	2.2×10 ⁻²	1.0×10 ⁻³	0.5		±1.1	1100
	98	105	32	10	36	38			280	560	6400	4.7×10 ⁻²	2.6×10 ⁻³			±1.3	1740

① 惯性力矩和重量按最大孔计算！



可选加工

选加工 代码	变更d/e孔径 dh() eh()	d孔侧键槽加工 DC	e孔侧键槽加工 DD																								
技术说明	 选型方法 dh3.1 eh4.5 ① 最小单位0.1 ② dh须≤eh ③ 选型时须将d(e) 变更为dh(eh)	<table><tr><th>D</th><th>dh-eh</th></tr><tr><td>15</td><td>3~6</td></tr><tr><td>19</td><td>4~8</td></tr><tr><td>25</td><td>5~12</td></tr><tr><td>27</td><td>5~14</td></tr><tr><td>34</td><td>6~16</td></tr><tr><td>39</td><td>8~20</td></tr><tr><td>44</td><td>8~22</td></tr><tr><td>56</td><td>10~28</td></tr><tr><td>64</td><td>15~35</td></tr><tr><td>79</td><td>20~42</td></tr><tr><td>98</td><td>25~50</td></tr></table> 	D	dh-eh	15	3~6	19	4~8	25	5~12	27	5~14	34	6~16	39	8~20	44	8~22	56	10~28	64	15~35	79	20~42	98	25~50	
	D	dh-eh																									
15	3~6																										
19	4~8																										
25	5~12																										
27	5~14																										
34	6~16																										
39	8~20																										
44	8~22																										
56	10~28																										
64	15~35																										
79	20~42																										
98	25~50																										
		选型方法 DC ❶ 不可与dh、eh可选加工共用。	选型方法 DD ❶ 不可与dh、eh可选加工共用。																								

① 当孔径≥6时才能选择键槽加工。

② 键槽加工尺寸请参阅联轴器“产品简介”。



请按图示订货

型号	代码	D	d-e
DBM52	98	25	25 28 30 32
		e	25 28 30 32...

DBM52—D98—d25—e28



未税价(元)

数量	1~9	10~
价格	100%	另行报价



交货期
7

☑ 可选加工

型号	代码	D	d-e	可选加工 代码
DBM52	98	25	25 28 30 32	dh eh
		e	25 28 30 32 35 38 40 42...	

DBM52—D98—dh25.1—eh28.5

☑ 可选加工

型号	代码	D	d-e	可选加工 代码
DBM52	98	25	25 28 30 32	DC DD
		e	25 28 30 32 35 38 40 42...	

DBM52—D98—d25—e28—DD