



英制管螺纹·60°外锥面密封·直接头

代码	类型	适用软管	材质
WSH21	直接头	编织软管	碳钢
WSH22			SUS304
WSH23		缠绕软管	碳钢
WSH24			SUS304




视角标准：第一视角



英制管螺纹·60°外锥面密封·90°弯接头

代码	类型	适用软管	材质
WSH26	90°弯接头	编织软管	碳钢
WSH27			SUS304
WSH28	90°弯接头	缠绕软管	碳钢
WSH29			SUS304



视角标准：第一视角




型号	规格	适用软管公称内径	G	A	S <sub>1</sub>	S <sub>2</sub>
WSH21	04	6	G1/4"×19	23	14	19
WSH22	06	10	G3/8"×19	25	17	22
WSH23	08	12	G5/8"×14	30	22	30
WSH23	12	20	G3/4"×14	32.5	27	32
WSH24	16	25	G1"×11	36.3	32	41
WSH24	20	32	G1.1/4"×11	41.5	41	50


型号	规格	适用软管公称内径	G	A	H	S
WSH26	04	6	G1/8"×28	30	34.5	14
WSH26	05	8	G1/4"×19	33	39.5	19
WSH27	06	10	G3/8"×19	35.3	43	22
WSH28	08	12	G1/2"×14	41	51	27
WSH29	10	16	G5/8"×14	56.5	56	30
WSH29	12	20	G3/4"×14	65.5	66	32

美制JIC螺纹·74°内锥面密封·直接头

代码	类型	适用软管	材质
WSH31	直接头	编织软管	碳钢
WSH32			SUS304
WSH33		缠绕软管	碳钢
WSH34			SUS304




视角标准：第一视角



美制JIC螺纹·74°外锥面密封·90°弯接头

代码	类型	适用软管	材质
WSH36	90°弯接头	编织软管	碳钢
WSH37			SUS304
WSH38	90°弯接头	缠绕软管	碳钢
WSH39			SUS304



视角标准：第一视角




型号	规格	适用软管公称内径	M	A	S <sub>1</sub>	S <sub>2</sub>
WSH31	04	6	7/16"×20	20	12	15
WSH32	06	10	9/16"×18	21	17	19
WSH33	08	12	7/8"×14	24	22	27
WSH33	12	20	1.1/16"×12	31.5	27	32
WSH34	16	25	1.5/16"×12	32.5	32	41
WSH34	20	32	1.7/16"×12	37	41	50


型号	规格	适用软管公称内径	M	A	H	S
WSH36	04	6	7/16"×20	30	33.5	15
WSH36	05	8	1/2"×20	33	37	17
WSH37	06	10	9/16"×18	35.3	39.3	19
WSH38	08	12	3/4"×16	41	47	24
WSH39	10	16	7/8"×14	56.5	52.5	27
WSH39	12	20	1.1/16"×12	65.5	63.5	32

美制ORFS螺纹·平面密封·直接头

代码	类型	适用软管	材质
WSH41	直接头	编织软管	碳钢
WSH42			SUS304
WSH43		缠绕软管	碳钢
WSH44			SUS304




视角标准：第一视角



美制ORFS螺纹·平面密封·90°弯接头

代码	类型	适用软管	材质
WSH46	90°弯接头	编织软管	碳钢
WSH47			SUS304
WSH48	90°弯接头	缠绕软管	碳钢
WSH49			SUS304



视角标准：第一视角



型号	规格	适用软管公称内径	M	A	S
WSH41	04	6	9/16"×18	22.5	19
WSH42	06	10	11/16"×16	25.5	22
WSH43	08	12	13/16"×16	28	27
WSH44	10	16	1"×14	33.5	30
WSH44	12	20	1.3/16"×12	35	36

型号	规格	适用软管公称内径	M	A	H	S
WSH46	04	6	9/16"×18	30	41	19
WSH46	06	10	11/16"×16	35.3	49.8	22
WSH47	08	12	13/16"×16	41	57	27
WSH48	10	16	1"×14	56.5	66	30
WSH49	12	20	1.3/16"×12	65.5	77	36

美制ORFS螺纹·平面密封·直接头

代码	规格	适用软管公称内径
WSH41	04	6
WSH42	06	10

WSH41-06



● 优惠价  
 数量 1~10 11~  
 价格 100% 另行报价

