


塔簧

代码	类型	材质		表面处理	旋转方向
		国标	相当		
YUE	塔簧	0Cr18Ni9	SUS304-WPB	—	向右
YWE		弹簧钢	SWP-A	发黑	

- ① 弹簧常数公差±10%;
- ② 两端均未进行磨削加工。



视角标准：第一视角

型号		自由长度 L	线径 d	外径 D ₁	有效圈数		F _{max}	允许负载 N _{max}		初始弹簧常数 N/mm		
代码	外径D				n	公差		SUS304-WPB	SWP-A	SUS304-WPB	SWP-A	
YUE YWE	9	8	0.5	4	5	±0.25	5	2.130	2.428	0.421	0.480	
	10	11			7	2.290	2.611	0.323	0.368			
		15			6.5	±0.5	10	2.700	3.078	0.245	0.279	
	11	20			7.5	±0.25	13	3.050	3.477	0.216	0.246	
		10	5	±0.25	7	3.440	3.922	0.470	0.536			
	12	13	5.5	0.6	5	5.5	±0.5	9	3.230	3.682	0.343	0.391
		17	6.5			±0.5	12	4.080	4.651	0.294	0.335	
		22	7.5			±0.25	15	4.370	4.982	0.255	0.291	
	13	12	5	0.8	6	5	±0.25	8	8.810	10.043	0.921	1.050
		16	5.5			±0.5	12	7.830	8.926	0.578	0.659	
	15	20	6.5	1	8	6.5	±0.5	14	8.530	9.724	0.490	0.559
		25	7.5			±0.25	17.5	9.700	11.058	0.382	0.435	
	18	15	5	1.2	10	5	±0.25	10.5	9.330	10.636	0.843	0.961
		19	5.5			±0.5	15	10.500	11.970	0.588	0.670	
	20	24	7	1.6	12	7	±0.5	16.8	9.960	11.354	0.461	0.526
		30	8.5			±0.25	21	11.900	13.566	0.382	0.435	
	22	20	5	1.6	12	5	±0.25	15	15.400	17.556	0.941	1.073
		25	5.5			±0.5	19	13.400	15.276	0.617	0.703	
	25	32	7	1.6	12	7	±0.5	23.5	15.000	17.100	0.480	0.547
		40	8.5			±0.25	28	15.000	17.100	0.402	0.458	
27	25	5	1.6	12	5	±0.25	17.5	23.600	26.904	1.670	1.904	
	30	5.5			±0.5	22.5	29.700	33.858	1.160	1.322		
30	37	7.5	1.6	12	7.5	±0.5	24.5	28.200	32.148	0.843	0.961	
	45	9			±0.25	29	28.500	32.490	0.706	0.805		



型号			
代码	外径D	自由长度L	线径d
YUE	9	8	0.5
YWE	10	11	0.5

YUE—D9—L8



数量	优惠价	
	1~9	10~
价格	100%	另行报价

交货期
5