

代码	类型		材质	内径公差	外径公差
OFK02	直柱型	标准型	高力黄铜(SP2)	E7	r6
OFL02		薄壁型	镶嵌固体润滑剂		




特点

- 自润滑、免维护，适用于重载、低速运动；
- 耐磨性优异，适用于直线、旋转、摇摆运动；
- 耐高温、低温，抗冲击性强。


① 与本产品相配轴径公差：d8重载、e7轻载、g6高精度(仅供参考)；

② 产品压入座孔时在座孔端部或者内壁涂抹少许润滑油，利用油压机或台钳将其慢慢压入座孔，请勿用力敲击产品，以免引起产品变形。


标准型
OFK02



A部(两端)放大图



薄壁型
OFL02



③ 与本产品相配固定座直径公差：H7(仅供参考)。

视角标准：第一视角

代码	型号		L								OFK02			OFL02					
	dE7		8	10	12	15	16	20	25	Df6	R	Df6	R						
标准型 OFK02	5	+0.032	8	10	12	15	16	20		9	+0.028								
	6	+0.020	8	10	12	15	16	20	25	10	+0.019								
	8	+0.040	8	10	12	15	16	20	25	12		0.5		0.3					
	10	+0.025	8	10	12	15	16	20	25	30	14	+0.034							
薄壁型 OFL02	12		8	10	12	15	16	20	25	30	18	+0.023							
	15	+0.050			10	12	15	16	20	25	30	40	21		1		0.4		
	16	+0.032			10	12	15	16	20	25	30	40	50	22	+0.041				
	20						15	16	20	25	30	40	50	28	+0.028				
	25	+0.061						15	16	20	25	30	40	50	33		1.5		0.5
	30	+0.040							15	16	20	25	30	40	50	38	+0.050		



请按图示订货

型号		L
代码	d	8 10
OFL02	6	8 10



未税价(元)

优惠价	
数量	1~9 10~
价格	100% 另行报价



交货期
7

