




① 3D模型仅供参考，具体尺寸请以参数表为准，注意选型。



① M=M3时, $d_1=\varnothing 6.5$ $d_2=\varnothing 3.5$
M=M4时, $d_1=\varnothing 8$ $d_2=\varnothing 4.5$

视角标准：第一视角

型号	皮带半径	dH7选择	D	D1	D2	h	W	L	T	T1	V	X	Y	M	适用皮带直径
代码	A														
20		4 5	16	22	18							5	3		
30	1	4 5 6 6.35 8	20	32	28	1	2.2	11	5	2.5		7	3.5	M3	2
40		4 5 6 6.35 8	20	42	38						2.5				
30		4 5 6 6.35 8	20	32	27			16				7	3.5	M3	
40	1.5	4 5 6 6.35 8	20	42	37	1.5	3.3								3
45		4 5 6 6.35 8 10 11 12	25	47	42						4.5	9	4.5	M4	
60		4 5 6 6.35 8 10 11 12	25	62	57			20							
23				25	19										
28		4 5 6 6.35 8	20	30	24			16			2.5	7	3.5	M3	
30		4 5 6 6.35 8	20	32	26										
40		4 5 6 6.35 8	20	42	36										4
45	2	4 5 6 6.35 8 10 11 12	25	47	41	2	4.4								
48		4 5 6 6.35 8 10 11 12	25	50	44			20			4.5	9	4.5	M4	
60		4 5 6 6.35 8 10 11 12	25	62	56										
80		4 5 6 6.35 8	20	82	76			16	10	5	2.5	7	3.5	M3	
28		4 5 6 6.35 8	20	30	23										
40		4 5 6 6.35 8	20	42	35										
48		4 5 6 6.35 8	20	50	43										
50	2.5	4 5 6 6.35 8 10 11 12	25	52	45	2.5	5.5	20			4.5	9	4.5	M4	5
60		4 5 6 6.35 8 10 11 12	25	62	55										
75		4 5 6 6.35 8	20	77	70										
80		4 5 6 6.35 8	20	82	75										
28		4 5 6 6.35 8	20	30	22			16			2.5	7	3.5	M3	
38		4 5 6 6.35	20	40	32							6.5			
48		4 5 6 6.35 8	20	50	42										
50		4 5 6 6.35 8	20	52	44										
58	3	4 5 6 6.35 8 10 11 12	25	60	52	3	6.6	20			4.5	9	4.5	M4	6
60		4 5 6 6.35 8 10 11 12	25	62	54										
75		4 5 6 6.35 8	20	77	69										
95		4 5 6 6.35 8	20	97	89										
100		4 5 6 6.35 8	20	102	94										

① 可选加工

型号	皮带半径	dH7选择
代码 A		
ENS01 20		4 5
ENS11 30		4 5 6 6.35 8

ENS01-A20-1-d5

型号	皮带半径	dH7选择	可选加工代码
代码 A			
ENS01 20		4 5	
ENS11 30		4 5 6 6.35 8	

ENS01-A20-1-d5-DC



数量	1~9	10~
价格	100% 另行报价	



1

请按图示订货

可选加工

代码	技术说明										
DC	切割D1尺寸 选型方法 DC ① 切割D1尺寸，减小外径； ② 外径切割的加工面可能不进行表面处理； ③ 适用皮带半径3.0以下规格； ④ 仅适用标准型产品。 <table> <tr> <th>适用皮带半径</th><th>DC</th></tr> <tr> <td>1</td><td>A+0.8</td></tr> <tr> <td>1.5</td><td>A+1.2</td></tr> <tr> <td>2</td><td>A+1.6</td></tr> <tr> <td>2.5</td><td>A+1.8</td></tr> </table>	适用皮带半径	DC	1	A+0.8	1.5	A+1.2	2	A+1.6	2.5	A+1.8
适用皮带半径	DC										
1	A+0.8										
1.5	A+1.2										
2	A+1.6										
2.5	A+1.8										