



碟形弹簧

标准型

代码	类型	材质		最大压缩量
		国标	相当	
Y-RAA11	标准型	0Cr18Ni9	SUS304	$h \times 75\%$



适用标准: DIN 2093

视角标准: 第一视角

代码	型号		d	全位移 h	总高度L		压缩量(F=h×75%)时 荷重
	D	厚度t					
Y-RAA11	8	0.3	4.2	0.25	0.55	±0.10	104
		0.4		0.2	0.6		184
	10	0.4	5.2	0.3	0.7		184
		0.5		0.25	0.75		290
	12.5	0.5	6.2	0.35	0.85		263
		0.7		0.3	1		592
	14	0.5	7.2	0.4	0.9		246
		0.8		0.3	1.1		713
	16	0.6	8.2	0.45	1.05		369
		0.9		0.35	1.25		925
	18	0.7	9.2	0.5	1.2		510
		1		0.4	1.4		1146
	20	0.8	10.2	0.55	1.35		669
		1.1		0.45	1.55		1367
	22.5	0.8	11.2	0.65	1.45		634
		1.25		0.5	1.75		1543
	25	0.9	12.2	0.7	1.6		775
		1.5		0.55	2.05		3176
	28	1	14.2	0.8	1.8		1014
		1.5		0.65	2.15		3088
	31.5	1.25	16.3	0.9	2.15		1543
		1.75		0.7	2.45		3794
	35.5	1.25	18.3	1	2.25		1367
		2		0.8	2.8		4676
40	1.5	20.4	1.15	2.65	2823		
	2.25		0.9	3.15	5471		
45	1.75	22.4	1.3	3.05	3529		
	2.5		1	3.5	6927		
50	2	25.4	1.4	3.4	4279		
	3		1.1	4.1	10766		

荷重为参考值。



请按图示订货

型号			
代码	D	厚度 t	d
Y-RAA11	10	0.5	4.2
	10	0.5	5.2

Y-RAA11—D8—t0.4



未税价(元)

● 优惠价

数量 1~99 100~

价格 100% 另行报价

